



**Pequonnock River Trail Crossings
Route 111 at Old Mine Road
Whitney Avenue at Pequonnock River Trail
Trumbull, Connecticut**

GENERAL SPECIFICATIONS

TOWN OF TRUMBULL, CONNECTICUT
GENERAL SPECIFICATIONS
INDEX

<u>ARTICLE</u>	<u>TITLE</u>	<u>PAGE</u>
1.	Index	1-2
2.	Bids	3
3.	Obligations Of Bidders	3
4.	Contract Documents	4
5.	Director of Public Works	4
6.	Town Engineer	4
7.	Contractor	4
8.	Sub-Contractor	4
9.	Notice	4
10.	Time Is Of The Essence	5
11.	Commencement Of Work	5
12.	Blank Form For Bid	5
13.	Working Hours And Holidays	6
14.	Performance & Guarantee Maintenance Bond	6
15.	Additional Or Substitute Bond	7
16.	Power Of Attorney	7
17.	Qualifications For Employment	7
18.	Payment Of Employees	7
19.	Delete	7
20.	Accident Prevention	8
21.	Inspection	8
22.	Payments	8
23.	General Specifications	8
24.	"(Or Equal Clauses)"	
25.	Inspection And Tests	9
26.	Cost And Tests	9
27.	Protection Of Work And Property	10
28.	Power Of Contractor To Act In An	10
29.	Emergency	
30.	Certificate Of Completion	10
31.	Final Payment	10
32.	Acceptance Of Final Payment	10
33.	Constitutes Release	
34.	Sub-Surface Structures	10
35.	Sub-Surface Conditions	11
36.	Contractor's Title To Materials	11
37.	Superintendence By Contractor	11
38.	Representations Of Contractors	11
39.	Patent Right	12
	Permits And Regulations	12
	Correction Of Work	12
	Statement Showing Amount Due For	
	Wages, Material And Supplies	13
	Town Right to Withhold Payments	13

<u>ARTICLE</u>	<u>TITLE</u>	<u>PAGE</u>
40.	Town Right To Stop Work Or Terminate Contract	13
41.	Uses Of Premises And Removal Of Debris	15
42.	All Work Subject To Control Of The Engineer	16
43.	Town Engineer, Control Not Limited	16
44.	Provisions Required By Law Deemed Inserted	16
45.	Subletting, Successor And Assigns	17
46.	Definitions	17
47.	Abbreviations	17
48.	Handling And Distribution	18
49.	Materials	18
50.	Watchman	19
51.	Maintenance Of Traffic	19
52.	Driveways And Property Entrances	20
53.	Dust	20
54.	Preservation Of Trees	20
55.	Inspection Of Work Away From The Site	20
56.	Contractor's Shop And Working Drawings	20
57.	Occupying Private Land	22
58.	Interference With And Protection of Streets	22
59.	Storage Of Materials And Equipment	22
60.	Insufficiency Of Safety Precautions	22
61.	Sanitary Regulations	23
62.	Delete	23
63.	Dimensions Of Existing Structures	23
64.	Work To Conform	23
65.	Computations of Quantities	23
66.	Planning and Progress Schedules	24
67.	Precautions During Adverse Weather	24
68.	As-Built Drawings	24
69.	Scope of Work	24
70.	Field Office	26
71.	Coordination Plans/Specifications	26
72.	No Payment	26
73.	Noise	26

TOWN OF TRUMBULL, CONNECTICUT

GENERAL SPECIFICATIONS

1. BIDS:

Bids, as stated in the "Bid Sheet", will be compared on the basis of the sum of the quantities multiplied by respective unit prices, added to lump-sum prices.

In the event that there is a discrepancy in the bid sheet between the lump-sum or unit prices written in words and figures, the prices written in words shall govern.

The Town agrees to examine and consider each bid submitted in consideration of the Bidder's Agreements, as hereinabove set forth in the Bid Sheet.

NOTE: Any/all reference to "he/him" shall be taken to mean "his/her/its".

2. OBLIGATION OF BIDDERS:

At the time of opening of bids, each bidder shall be presumed to have inspected the sites, and to have read and made himself thoroughly familiar with the Plans and Contract Documents including all addenda. The failure or omission of any bidder to receive or examine any form, instrument or document shall in no way relieve any bidder from any obligation in respect to his bid.

Each bidder must fully inform himself of the construction and labor conditions relating to the work which is now or will be performed. Failure to do so will not relieve the successful bidder of his obligation to furnish all labor and materials necessary to carry out the provisions of the contract documents and to complete the contemplated work. Inasmuch as possible, the contractor must, in carrying out his work, employ such methods or means as will not cause any interruptions or interference with the work of any other contractor.

The successful bidder must furnish a field and office organization chart and equipment list to be used on the job to demonstrate that he has the capability to perform the work prescribed for this project and shall furnish the Town all other information and data requested on the form provided for this purpose; such submission to be made prior to construction startup.

The Contractor shall supply a foreman full time on the job. Such foreman must be satisfactory to the Town of Trumbull. Failure to comply shall be cause for breach of contract.

The Contractor's normal sequence of operation in performing the work under the terms of this contract shall be varied at the direction of the Town of Trumbull, so that priorities can be given in critical areas such as schedule, right-of-way, clearance and other Town commitments, either present or future.

The Contractor shall file an appeal to the Public Works Director if the sequence of operation in performing the work is varied by the Town in a manner that is unacceptable to him.

The Contractor shall have no claim against the Town for damages or extra compensation on account of delays in execution of the work or delays in making the construction site available to the Contractor.

3. CONTRACT DOCUMENTS:

Whenever the term "Contract Documents" is used herein, it shall include the Agreement, Information to Bidders, General Specifications, Bid Documents, Technical Specifications, Special Notes, Addenda, and Project Plans, including all modifications thereof incorporated in the documents before their execution.

4. DIRECTOR OF PUBLIC WORKS:

The Director Public Works, of the Town of Trumbull, Connecticut, under whose authority all public works are performed. Hereinafter when the word "Engineer" is used, it is hereby interpreted to include the authority of the Director of Public Works, as well as the Town Engineer.

5. TOWN ENGINEER:

The Town Engineer will represent the Town of Trumbull, Connecticut, and shall have complete charge of all work involved. Hereinafter where the word "Engineer" appears it shall mean the Town Engineer or his duly authorized representatives performing their usual duties, i.e. clerk of the works, etc.

6. CONTRACTOR:

Party of the second part to the contract, acting directly or through his agent or employees.

7. SUB-CONTRACTOR:

Any individual, firm, partnership or corporation to whom the Contractor sub-lets or assigns any part or parts of this project covered by this contract.

8. NOTICE:

The term "notice" as used herein shall mean and include written notices.

Written notice shall be deemed to have been served, when deposited in a United States Mail Box to or at last known business address of the person, firm or corporation for whom intended, or to his or their or its duly authorized agent, representative or office,

or enclosed in a postage prepaid wrapper or envelope addressed to such person or firm or corporation at his or their or its last known business address

9. TIME IS OF THE ESSENCE:

Time is of the essence for this contract and as execution of the work may inconvenience property owners, vehicular traffic, pedestrians and adversely affect business in the area, it is essential that the work be pressed vigorously to completion. Also the cost of Town administration and supervision of construction, will be increased as the time occupied in the work is lengthened, and the deprivation to the residents of the Town of the needed improvement on herein contract may cause damages to the Town.

In the event the Contractor fails to perform the work in a timely manner due to the Contractor's poor planning, financial status, errors in construction or any other reason directly attributed to the Contractor's circumstances, the Town may institute default proceedings against the Contractor to recover damages and losses. Any payments due the Contractor may be withheld pending final determinations, and the bonding company for the performance of the work on this contract may be notified of impending actions that may be warranted.

If any delay is imposed on the Contractor by specific orders of the Engineer, ie; to stop the work (for reasons other than failure on the part of the Contractor to comply with the requirements of the Contract Documents), material or labor strikes, acts of God, etc., such delay will entitle the Contractor to an equivalent extension of time.

When extra or additional work is ordered by the Engineer, the Contractor will be allowed an extension of time expressed in days as determined by the Town Engineer. The Contractor shall submit a written request for an extension of time, along with reasons for the request. A written response will be transmitted to the Contractor with a determination by the Town as to whether or not an extension of time will be granted.

10. COMMENCEMENT OF WORK:

The Contractor shall commence work on the day specified in the order by the Engineer, as the date of such commencement; and shall fully complete the work within the number of consecutive calendar days from said date as hereinafter specified as the period for completion of his contract, unless such period shall be extended as hereinafter provided by the Town.

11. BLANK FORM FOR BID:

All bids must be written or typed upon the blank form for "Bid Sheet," and must state the proposed price of each item of the work, both in words and in figures, and must be signed by the bidder with his business address.

BIDDERS SHALL NOT REMOVE AND SUBMIT THE BID PAGES SEPARATE FROM THE VOLUME OF CONTRACT DOCUMENTS, BUT SHALL SUBMIT THEIR BIDS BOUND WITH THE COMPLETE VOLUME OF ATTACHED DOCUMENTS,

The undersigned understands that information relative to subsurface and other conditions, natural phenomena, existing pipes and other structures (surface and/or subsurface) has been furnished only for his information and convenience without any warranty of guarantee, express or implied, that the subsurface and/or other structures (surface and/or subsurface) actually encountered will be the same as these shown on the drawings or in any of the other contract documents and he agrees that he shall not use or be entitled to use any such information made available to him through the contract documents or otherwise or obtained by him in his own examination of the site, as a basis of or ground for any claim against the Town, arising from or by reason of any variance which may exist between the aforesaid information made available to or acquired by him and the subsurface and/or other conditions, natural phenomena, existing pipes and other structures (surface and/or subsurface) actually encountered during the construction work, and he has made due allowance therefore in this bid.

12. WORKING HOURS AND HOLIDAYS:

The Contractor shall perform no work during the Town of Trumbull's employees' holidays nor before or after the Town's normal working hours, without specific approval of the Director.

The normal working hours of the Town are Monday through Friday, 7:00 a.m. to 4:00 p.m.

THE OFFICIAL TOWN OF TRUMBULL HOLIDAYS ARE:

New Year's Day
Martin Luther King Day
Presidents' Day
Good Friday
Memorial Day
Independence Day
Labor Day
Columbus Day
Veteran's Day
Thanksgiving Day
Day Following Thanksgiving Day
Christmas Day
Day After Christmas Day (2014 Floating Holiday)

13. PERFORMANCE & GUARANTEE MAINTENANCE BOND:

OMITTED

14. ADDITIONAL OR SUBSTITUTE BOND:

If at any time the Town becomes dissatisfied with the performance bond as issued by the present surety or sureties, or if for any other reason such bond shall cease to be adequate surety to the Town, the Contractor shall within five (5) days after notice from the Town to do so, substitute an acceptable bond in such form and sum and signed by such other sureties as may be satisfactory to the Town.

The premium on such bonds shall be paid by the Contractor. No further payment shall be deemed due nor shall be made until new sureties shall have qualified.

15. POWER OF ATTORNEY:

Attorneys-in-fact who sign contract bonds must file with each bond a certified copy of their power of attorney to sign said bond.

16. QUALIFICATIONS FOR EMPLOYMENT:

No person under the age of sixteen (16) years and no person currently serving sentences in a penal or Correctional institution shall be employed to perform any work on the project under this contract.

No person whose age or physical condition is such as to make his employment dangerous to his health or safety or to the health and safety of others shall be employed to perform any work on the project under this contract.

Provided that this sentence shall not operate against the employment of physically handicapped persons otherwise employed where such persons may be safely assigned to work, which they can ably perform.

There shall be no discrimination because of race, creed, color or political affiliation in employment of persons for work on the project under this contract.

17. PAYMENT OF EMPLOYEES:

The Contractor and each of his subcontractors shall pay each of his employees engaged in the work on the project under this contract in full (less deductions made mandatory by law) in a timely and routine manner.

18. DELETE

19. ACCIDENT PREVENTION:

Precaution shall be exercised at all times for the protection of all persons (including employees) and property.

The safety provisions of applicable laws, building and construction codes shall be observed.

Reference is hereby made to Occupational Safety and Health Administration standards as described in OSHA 2206, 1983 or latest edition or revision thereof

Machinery, equipment and all hazards shall be guarded or eliminated in accordance with the safety provisions of the manual of "Accident Prevention in Construction", published by the Associated General Contractors of America, to the extent that such provisions are not in contravention of applicable laws.

20. INSPECTION:

The Engineer or his authorized representative shall be permitted to inspect the work, materials, payrolls, and records of personnel, invoices of material and other relevant data and records of this contract.

21. PAYMENTS:

The Town's terms of payment are Net 30 Days after approval of invoice. No invoice will be paid until acceptance of goods ordered. By the fifth (5th) day of each month application for payment must be submitted by the Contractor to the Town's designated field representative, for verification and approval of quantities and costs incurred during said pay period. Only upon approval by designated representative will payment be forwarded for processing.

The Town shall retain five per centum (5%) of each estimate until final completion and acceptance of all work covered by this contract.

22. GENERAL SPECIFICATIONS "(OR EQUAL CLASSES)":

Whenever in this contract or specifications, a particular brand or make of material, device or equipment is shown or specified, such brand, make of material, device or equipment should be regarded merely as a standard unless otherwise specified.

If three or more brands, makes of material, devices or equipment are shown or specified, each should be regarded as the equal of the others.

When in the opinion of the Engineer, or his authorized agent, any other brand, make of material, device or equipment is recognized as equal to that specified, considering quality, workmanship and economy of operation, and suitable for the purpose intended, it will be accepted.

In the opinion of the Engineer and the Town's duly authorized agents, all material and workmanship shall in every respect be in accordance with what is in conformity with approved modern practice.

Whenever the plans, drawings, specifications, other contract documents, or the quality of the work, admit of doubt as to what is permissible, the interpretation will be made by the Engineer, as to which is in accordance with approved modern practice, in order to meet the particular requirements of the contract.

In all cases, new material shall be used unless this provision is waived with a special written notice by the Engineer.

23. INSPECTION AND TESTS:

All material and workmanship (if not otherwise designated) shall be subject to inspection, examination and tests, by the Engineer, or his duly authorized representatives, at any and at all times during the manufacture and/or construction, and at any and all places where such manufacture or construction is carried on.

Without additional charge, the Contractor shall furnish promptly all reasonable facilities, labor and material necessary to make tests so required, safe and convenient.

Special full size and performance tests shall be conducted as described in the specifications.

If at any time before final acceptance of the entire work, the Engineer considers necessary or advisable any examination of any portion of the work already completed, by removing or tearing out the same, the Contractor shall upon request, furnish promptly all necessary facilities, labor and materials.

If such work is found to be defective in any material respect, due to material or faulty construction by the Contractor, or any subcontractor, or if any work shall be covered over without approval of the engineer (whether or not the same shall be defective) the Contractor shall be liable for the expense of such examination and of satisfactory reconstruction.

If, however, such approval and consent shall have been given and if such work is found to meet the requirements of this contract, the Contractor shall be recompensed for the extent of such examination and reconstruction in the manner herein provided for the payment of the cost of "EXTRA WORK."

24. COSTS AND TESTS:

The selection of Bureau Laboratories, and/or agencies for the inspection and tests of supplies, materials or equipment shall be subject to the direction of the Engineer.

If inspection, tests, analysis of the materials or equipment, should disclose that said material or equipment requires rejection, then the cost of said inspection, test analysis shall be borne by the Contractor and said cost shall be deducted from the Contractor's current estimate by the Engineer. If supplies, material or equipment shall be found acceptable, the cost of said inspection, tests or analysis shall be borne by the Town.

25. PROTECTION OF WORK AND PROPERTY:

The Contractor shall at all times safely guard the Town's property from injury or loss, in connection with this contract. He shall at all times safely guard and protect his own work and that of adjacent property from damage. The Contractor shall replace and make good any such damage, loss or injury. All passageways, guard fences, lights and

other facilities required for protection by local conditions must be provided and maintained.

26. POWER OF CONTRACTOR TO ACT IN AN EMERGENCY:

In case of an emergency, which threatens loss or injury of property and/or safety of life, the Contractor shall be allowed to act without previous instructions from the Engineer, as he sees fit. He shall notify the Engineer immediately thereafter of any compensation claimed by the Contractor due to such extra work, and shall submit same to the Engineer for approval. When the Contractor has not taken action, but has notified the Engineer of an emergency threatening injury to persons or damage to the work, or any adjoining property, the Contractor shall act as instructed or authorized by the Engineer to prevent such threatened injury or damage.

27. CERTIFICATE OF COMPLETION:

Upon completion of all work whatsoever required, the Engineer shall file a written certificate with the Director of Finance and the Contractor, for the entire amount of work performed and compensation earned by the Contractor, including extra work and compensation thereof.

28. FINAL PAYMENT:

Within thirty days of filing a certificate of completion, the Town shall pay to the Contractor the amount therein stated, less all prior payments and advances whatsoever to or for the account of the Contractor. All prior estimates and payments, including those relating to extra work, shall be subject to correction by this present payment, which throughout this contract is called the FINAL PAYMENT.

29. ACCEPTANCE OF FINAL PAYMENT CONSTITUTES RELEASE:

The acceptance by the Contractor of the final payment, shall be and shall operate as a release to the Town of all claims and of all liability to the contract or for all things done or furnished in connection with this work, and for every act and neglect of the Town and others relating to or arising out of this work, accepting the Contractor's claim for interest upon the final payment, if the payment is improperly delayed. No payment, however, final or otherwise, shall release the Contractor or his sureties from any obligation under this contract or of the performance bond.

30. SUB-SURFACE STRUCTURES:

All sub-surface structures and public utility lines have been located as far as possible, as indicated on the plans and information obtained from the respective utilities. The Town does not assume the responsibility for the accuracy of this information.

31. SUB-SURFACE CONDITIONS:

Bidders are notified that it is obligatory for them to obtain all the information they require as to the existing physical conditions relative to the work and in particular to sub-surface conditions---NOR SHALL THE TOWN BE HELD LIABLE FOR ANY ADDITIONAL COST TO THE CONSTRUCTION WHICH MAY RESULT DUE TO THESE CONDITIONS, and each bidder in bidding must rely exclusively upon his own

investigation and that he makes this bid with the full knowledge of the kind, quality and quantity of work required.

The undersigned understands that information relative to subsurface and other conditions, natural phenomena, existing pipes and other structures (surface and/or subsurface) has been furnished only for his information and convenience without any warranty of guarantee, express or implied, that the subsurface and/or other structures (surface and/or subsurface) actually encountered will be the same as these shown on the drawings or in any of the other contract documents and he agrees that he shall not use or be entitled to use any such information made available to him through the contract documents or otherwise or obtained by him in his own examination of the site, as a basis of or ground for any claim against the Town, arising from or by reason of any variance which may exist between the aforesaid information made available to or acquired by him and the subsurface and/or other conditions, natural phenomena, existing pipes and other structures (surface and/or subsurface) actually encountered during the construction work, and he has made due allowance therefore in this bid.

32. CONTRACTOR'S TITLE TO MATERIALS:

No materials or supplies for the work shall be purchased by the Contractor or sub-contractor, subject to any chattel mortgage or under any conditional sale or other agreement for which interest is retained by the seller.

33. SUPERINTENDENCE BY CONTRACTOR:

The Contractor shall employ a project Super-intendant who shall be present full time at the site of the work and who shall have full authority to act for the Contractor. The Contractor shall employ a project foreman who shall be in attendance at the work site during working hours.

It is understood that such representative shall be acceptable to the Town and shall be one whose experience and length of service in this particular kind of work warrants his ability to perform the duties entailed to the satisfaction of the Engineer, and who can continue in that capacity for the particular job involved unless he ceases to be on the Contractor's payroll.

The Engineer reserves the right of investigation to satisfy the Town that the appointed superintendent is properly qualified to carry out the obligations entailed to perform the work herein contemplated in the plans and specifications and directions.

34. REPRESENTATIONS OF CONTRACTORS:

The Contractor represents and warrants:

- a). That he is financially solvent and that he is experienced in and competent to perform the type of work, or to furnish plant and equipment materials and supplies.
- b). That he is familiar with all Federal, State and Municipal laws, ordinances and regulations, which in any way may affect the work of those employed therein.
- c). That he has carefully examined the plans and specifications and the site of the work, and that from his own investigation he has satisfied himself about the nature and location

of the work, character, quality and quantity of the surface and sub-surface materials likely to be encountered, as well as the character of equipment and other facilities needed for the performance of the work, the general local conditions and all other conditions which may in any way affect the work.

35. PATENT RIGHT:

As part of his obligation hereunder and without any additional compensation, the Contractor will pay for all patent fees or royalties required in respect to the work or any part thereof, and will fully indemnify the Town for any loss on account of infringement of any patent rights.

36. PERMITS AND REGULATIONS:

The Contractor shall procure and pay for all permits and licenses necessary for the execution of his work. Town permit fees will be waived.

The Contractor shall comply with all laws, ordinances, rules and regulations relating to the performance of the work.

37. CORRECTION OF WORK:

All work, all material, whether incorporated in the work or not, all processes of manufacture and all methods of construction, shall be at all time and places subject to the inspection of the Engineer, who shall be the final judge of the quality and suitability of the work, materials, processes of manufacture and methods of construction for the purpose for which they are used.

Should they fail to meet the approval of the Engineer they shall be forthwith reconstructed, made good, replaced and corrected, as the case may be, by the Contractor, at his own expense.

Rejected material shall immediately be removed from the site.

Acceptance of material and workmanship by the Inspectors shall not relieve the Contractor from his obligation to supply other materials and workmanship when so ordered by the Engineer.

If, in the opinion of the Engineer, it is undesirable to replace any defective or damaged material, or to reconstruct or correct any portion of the work injured or not performed in accordance with the contract, the compensation to be paid to the Contractor hereunder, shall be reduced by such amount which the Engineer deems equitable.

The Contractor expressly warrants that his work shall be free from any defects in material or workmanship, and agrees to correct any such defects which may appear within the maintenance period, following final completion of work.

Neither acceptance of the completed work, nor payment thereof, shall operate to release the Contractor or his sureties from any obligation under or upon this contract or the performance bond.

38. STATEMENT SHOWING AMOUNT DUE FOR WAGES, MATERIAL ANDSUPPLIES:

With each application for payment under this contract, the Contractor and every subcontractor shall deliver to the Town a written verified statement in a form satisfactory to the Town, showing in detail the amounts then due and unpaid by such Contractor or subcontractor, to all laborers for daily or weekly wages, men employed by him under the contract for performance of work at the site thereof, or to other persons for material and equipment delivered at the site of the work.

The term "laborers" as used herein, shall include workmen and mechanics.

39. TOWN RIGHT TO WITHHOLD PAYMENTS:

The Town may withhold from the Contractor as much of any approved payment due him, as the Town deems necessary.

1st. To assure the payment of just claims due and unpaid of any person supplying labor or materials for the work.

2nd. To protect the Town from loss due to defective work not remedied.

or

3rd. To protect the Town from loss due to injury to persons or damage to work or property of other Contractors, subcontractors, or others caused by the act or neglect of the Contractor or any of his subcontractors.

The Town shall have the right, as agent for the Contractor, to apply any such amounts so withheld in such manner as the Town may deem proper, to satisfy such claims or to secure such protection.

Distribution of such money shall be considered as payments for the amount of the Contractor.

40. TOWN RIGHT TO STOP WORK OR TERMINATE CONTRACT:

If the Contractor shall be adjudged bankrupt, an assignment shall be made for the benefit of creditors. A receiver or liquidator shall be appointed for the Contractor and for any of his property. The Contractor shall be dismissed within twenty (20) days after such appointment. The proceedings in connection therewith shall not be stayed within the said twenty (20) days. If the Contractor shall refuse or fail after notice or warning from the

Engineer, to supply enough properly skilled workmen or proper materials, or if the Contractor shall fail to prosecute the work or any part thereof with such diligence as will insure its completion within the period herein specified (or duly authorized extension thereof) or shall fail to complete the work within said period, or if the Contractor shall fail to make prompt payment to persons supplying labor or materials for the work, or if the Contractor shall fail or refuse to regard laws, ordinances or the instructions of the Engineer or otherwise be guilty of a substantial violation of any provision of this contract, then in any such event, the Town without prejudice to any other right or remedy, may give seven (7) days notice to the Contractor, to terminate the employment of the Contractor. The Contractor shall lose the right to proceed either for the entire work or (at the option of

the Town) for any portion thereof on which delays shall have occurred. The Town may as it deems expedient take possession of the work and complete it by contract or otherwise.

In such cases, the Contractor shall not be entitled to receive any further payment until the work is finished.

If the unpaid balance of the compensation to be paid the Contractor hereunder, shall exceed the expense of so completing the work (including compensation for additional managerial administrative and inspection services and any damages for delay), such excess shall be paid to the Contractor.

If such expense shall exceed such unpaid balance, the Contractor and his sureties shall be liable to the Town for such excess.

If the right of the Contractor to proceed with the work is so terminated, the Town may take possession of and utilize in completing the work, such materials, appliances, supplies, plant and equipment as may be on the site of the work, and necessary therefore.

If the work shall be stopped by order of the Court or any other public authority, for a period of three (3) months, without act or fault of the Contractor or any of his agents, servants, employees, or subcontractors, the Contractor may upon ten (10) days' notice to the Town of Trumbull, discontinue his performance of the work and/or terminate the contract.

TERMINATION:

A. TERMINATION FOR CAUSE, If through any case, the Contractor shall fail to fulfill in a timely manner, its obligations under this Agreement, or if the contractor shall violate any of the covenants, agreements, or stipulations of this Agreement, the Town shall thereupon have the right to terminate this Agreement for cause by giving written notice to the Contractor of such termination and specifying the effective date thereof, at least five (5) days before the effective date of such termination. In the event, all finished or unfinished reports, documents, data, studies, surveys, drawings, maps, models, photographs, and reports or other material prepared by the contractor shall be entitled to receive just and equitable compensation for any satisfactory work completed on such documents and other materials to the effective date of termination.

The term "cause" includes, without limitation the following:

- 1) If the Contractor furnished any statement, representation, warranty or certification in connection with this Agreement, which is materially false, deceptive, incorrect, or incomplete.
- 2) If the Contractor fails to perform to the Town's satisfaction any material requirement of the Agreement, or is in violation of any specific provision thereof.

- 3) If the Town reasonably determines satisfactory performance of the Agreement is substantially endangered or can reasonably anticipate such an occurrence or default.

Notwithstanding the above, the Contractor shall not be relieved of liability to the Town for any damages sustained by the Town by virtue of any breach of the Agreement by the Contractor, and the Town may withhold any payment to the Contractor for the purpose of setoff until such time as the exact amount of damages due the Town from the Contractor is determined.

B. TERMINATION FOR CONVENIENCE: The Town may terminate this Agreement at any time the Town determines that the purposes of the distribution of monies under the agreement would no longer be served by completion of the Work/Project. The Town shall effect such termination by giving written notice of termination to the Contractor and specifying the effective date thereof, at least twenty (20) days before the effective date of such termination. In the event, all finished or unfinished documents and other materials as described in Subsection A shall, at the option of the Town, become its property. If the Agreement is terminated by the Town as provided herein, the Contractor shall be paid an amount which bears the same ratio to the total compensation as the services actually and satisfactorily performed to the effective date of termination bear to the total services of the Contractor pursuant to the terms of this Agreement, less payments of compensation previously made, and subject to the Town's right of set off for any damages pursuant to the terms of the Agreement.

41. USES OF PREMISES AND REMOVAL OF DEBRIS:

The Contractor undertakes at his own expense:

- a). To take every precaution against injuries to persons or damage to property.
- b). To store his apparatus, materials, supplies and equipment in such orderly fashion at the site of the work as will not unduly interfere with the progress of his work.
- c). To place upon the work area or any part thereof, only such loads as are consistent with the safety of that portion of the work.
- d). To frequently clean up all refuse, rubbish, scrap material and debris caused by his operations, so that the site of the work shall at all times present a neat, orderly and workmanlike appearance. Failure to comply with this article within 24 hours of notification

may result in the Owner having the work performed by outside sources at the Contractor's expense. These expenses will be deducted from the regular monthly periodic estimate.

- e). To remove before final payment all surplus materials, false work, temporary structures, (including foundations thereof), plant of any description and debris of every nature resulting from his operation, and to put the site in a neat and orderly condition.

f). To effect all cutting, fitting or patching of his work required to make the same conform to the plans and specifications, and with the consent of the Engineer, to cut or otherwise alter the work of any other Contractor.

42. ALL WORK SUBJECT TO CONTROL OF THE ENGINEER:

In the performance of the work, the Contractor shall abide by all orders, directions and requirements of the Engineer and shall perform all duties to the satisfaction of the Engineer, and at such time and places, by such methods and in such manner and sequence as the Engineer may require.

The Engineer shall determine the amount, quantity, acceptability and fitness of all parts of the work, shall interpret the plans, specifications, contract and any extra work orders, and shall decide all other questions in connection with the work.

The Contractor shall employ no plant, equipment, materials, methods or men to which the Engineer objects, and shall remove no plant materials, equipment or other facilities from the site of the work, without the Engineer's permission. Upon request, the Engineer shall confirm in writing any oral order, direction requirement or determination.

43. TOWN ENGINEER, CONTROL NOT LIMITED:

The enumeration herein or elsewhere in the contract of particular instances in which the opinion, judgment, discretion or determination of the Engineer, shall control or in which work shall be performed to his or their satisfaction as subject to his or their approval or inspection, shall not imply that only matters similar to those enumerated shall be governed and performed, but without exception all the work shall be governed and so performed.

44. PROVISIONS REQUIRED BY LAW DEEMED INSERTED:

Each and every provision of law and clause required by law to be inserted in this contract, shall be deemed to be inserted herein, and the contract shall be read and enforced as though it were included herein, and if through mistake or otherwise any such provision is not correctly inserted, then upon the application of either party, the contract shall forthwith be physically amended to make such insertion.

45. SUBLETTING, SUCCESSOR AND ASSIGNS:

The Contractor shall not sublet any part of the work under this contract, nor assign any moneys due him hereunder without first obtaining the written consent of the Town.

46. DEFINITIONS:

Wherever the words defined in this section or pronouns used in their stead occur in the specifications, they shall have the meanings herein given.

AS DIRECTED, AS REQUIRED, ETC.

Wherever in the specifications, or on the drawings the words "As Directed", "As Ordered", "As Requested", "As Required", "As Permitted", or words of like import are used, it shall be understood that the Direction, Order, Request, Requirement, or Permission of the Engineer is intended. Similarly, the words "Approved", "Accepted", "Satisfactory", and words of like import shall mean Approved by, Acceptable to, or Satisfactory to the Engineer.

ELEVATION

The figures given on the drawings or in the other contract documents after the word "Elevation" or abbreviation of it shall mean the Distance in Feet Above the Datum Adopted by the Engineer.

NOTE: Unless otherwise stated elsewhere in the contract documents and/or on the contract drawings, vertical elevation datum for this project is based upon NEW City Datum, NGVD (ele. 0.00 = mean water).

ROCK

The word "Rock" wherever used as the name of any excavated material or material to be excavated, shall mean only boulders or solid ledge rock which, in the opinion of the Engineer, requires, for its removal, drilling and blasting, wedging, sledging, barring or breaking up with a power operated tool. No soft or disintegrated rock which can be removed with a hand pick or power-operated excavator or shovel, no loose, shaken or previously blasted rock or broken stone in rock fillings or elsewhere, and no rock exterior to the maximum limits of measurement allowed, which may fall into the excavation, will be measured or allowed as "Rocks".

EARTH

The word "Earth", wherever used as the name of an excavated material or material to be excavated, shall mean all kinds of material other than rock as above defined.

47. ABBREVIATIONS:

Where any of the following abbreviations are used in the Specifications, they shall have the meaning set forth opposite each.

AASHO	American Association of State Highway Officials
ACI	American Concrete Institute
AISC	American Institute of Steel Construction
ASA	American Standard Association
ASCE	American Society of Civil Engineers
ASTM	American Society For Testing and Materials
NEC	National Electrical Code, Latest Edition

48. HANDLING AND DISTRIBUTION:

The Contractor shall handle, haul and distribute all materials and all surplus materials on the different portions of the work, as necessary or required; shall provide suitable and adequate storage room for materials and equipment during the progress of the work, and shall be responsible for the protection, loss of, or damage to materials and equipment furnished by him, until the final completion and acceptance of the work.

Storage and Demurrage charges by Transportation Companies and Vendors shall be borne by the Contractor.

49. MATERIALS:

Samples - Inspection - Approval, unless otherwise expressly provided on the Drawings or in any of the other contract documents, only new material and equipment shall be incorporated in the work. All materials and equipment furnished by the Contractor to be incorporated in the work shall be subject to the inspection and approval of the Engineer. No material shall be processed or fabricated for the work or delivered to the work site without prior approval of the Engineer.

As soon as possible after execution of the Agreement, the Contractor shall submit to the Engineer the names and addresses of the manufacturers and suppliers of all materials and equipment he proposes to incorporate into the work. When shop and working drawings are required as specified below, the Contractor shall submit prior to the submission of such drawings, data in sufficient detail to enable the Engineer to determine whether the manufacturer and/or supplier have the ability to furnish a product meeting the specifications. As requested, the Contractor shall also submit data relating to the materials and equipment he proposes to incorporate into the work in sufficient detail to enable the Engineer to identify and evaluate the particular product and to determine whether it confirms to the Contract Requirements. Such data shall be submitted in a manner similar to that specified for submission of shop and working drawings.

Facilities and labor for the storage, handling and inspection of all materials and equipment shall be furnished by the Contractor. Defective materials and equipment shall be removed immediately from the site of the work.

If the Engineer so requires, either prior to or after commencement of the work, the Contractor shall submit additional samples of materials for such special tests as the Engineer deems necessary to demonstrate that they conform to the specifications. Such samples, including concrete test cylinders, shall be furnished, taken, stored, placed and shipped by the approved molds for making concrete test cylinders. Except as otherwise expressly specified, with technical specifications, the Town shall make

arrangements and pay for the tests.

All samples shall be packed so as to reach their destination in good condition, and shall be labeled to indicate the material represented. The name of the building or work and location for which the material is intended and the name of the contractor submitting the sample. To ensure consideration of samples, the Contractor shall notify the Engineer by letter that the samples have been shipped and shall properly describe the samples in the letter. The letter of notification shall be sent separate from and should not be enclosed with the samples.

The Contractor shall submit data and samples, or place his orders, sufficiently early to permit consideration, inspection, testing and approval before the materials and equipment are needed for incorporation in the work. The consequence of his failure to do so shall be the Contractor's sole responsibility.

When required, the Contractor shall furnish to the Engineer triplicate sworn copies of manufacturer's shop or mill tests (or reports from independent test laboratories) relative to materials, equipment, performance rating and concrete data.

50. WATCHMAN:

If it becomes necessary to supply watchmen during non-regular working hours, they shall be employed until (in the opinion of the Engineer) their services are no longer required. The Contractor shall employ and pay a satisfactory, sober, able-bodied watchman who shall be in attendance upon the work at all times, (regardless of the hour) whenever work by the regular employees stops.

51. MAINTENANCE OF TRAFFIC:

The Contractor shall conduct his operations in such a manner so that he does not impose unnecessary hardship upon the residents along the route of the work.

Streets may be closed to traffic only upon written order of the Traffic Engineer. Traffic shall be maintained within the project area except where it is found impracticable, or seriously interferes with the Contractor's operations. If permanent repairs are not completed immediately, the pavement surface along the line of work shall be maintained in a condition comparable to the adjacent road surface.

People living or having business within the barricaded zone shall be permitted to use the highway for auto traffic if possible.

The Contractor shall protect all phases of the work from damage due to traffic, etc., and provide necessary watchmen, signalmen and (if so ordered by the Engineer) police officers.

No direct payment for maintenance of traffic will be made, but shall be considered as included in the base bid submitted.

52. DRIVEWAYS AND PROPERTY ENTRANCES:

Excavated materials and equipment shall be placed in such position as not to unnecessarily impede travel on the streets, or access to driveways. A sufficiently clear space for pedestrian travel shall be maintained on the sidewalks, and all property entrances and driveways shall be kept clear, where possible.

Where necessary, bridges shall be constructed and maintained for residents. Before closing any driveway or entrance, the Contractor shall give the owner or resident of the property involved, due notice of such temporary closing. When this is not

practicable and an emergency arises, the Contractor shall, on the order of the Engineer, provide a satisfactory place to house temporarily, any motor vehicle, which may be prevented from being housed at night.

No direct payment will be allowed for this work or condition, but shall be considered as included in the base bid submitted.

53. DUST:

The Contractor shall at all times during the execution of this contract, control the nuisance of flying dust, by water sprinkling or by application of oil, or a method satisfactory to the Engineer.

54. PRESERVATION OF TREES:

Trees and shrubs on the site of the work shall be protected during the entire period of the contract, and if injured by the Contractor or his employees, shall be replaced, unless it is covered by the bid items, at his expense before the completion of the contract.

55. INSPECTION OF WORK AWAY FROM THE SITE:

If work to be done away from the construction site is to be inspected on behalf of the Town during its fabrication, manufacture, or testing, or before shipment, the Contractor shall give notice to the Engineer of the place and time where such fabrication, manufacture, testing or shipping is to be done. Such notice shall be in writing and delivered to the Engineer in ample time so that the necessary arrangements for the inspection can be made.

56. CONTRACTOR'S SHOP AND WORKING DRAWINGS:

The Contractor shall submit for approval (in reproducible form unless otherwise specified) shop and working drawings of concrete reinforcement, structural details, piping layout, wiring, materials fabricated for the contract and materials and equipment for which such drawings are specifically requested.

Such drawings shall show the principal dimensions, weight, structural and operating features, space required, clearances, type and/or brand of finish or shop coat, grease fittings, etc., depending on the subject of the drawing, when it is customary to do

so. When the dimensions are of particular importance, or when so specified, the drawings shall be certified by the manufacturer or fabricator as correct for the contract.

When so specified or if considered by the Engineer to be acceptable, manufacturer's specifications, catalog data, descriptive matter, illustrations, etc., may be submitted for approval in place of shop and working drawings. In such case, requirements shall be as specified for shop and working drawings, insofar as applicable, except that the submission shall be in quadruplicate.

The Contractor shall be responsible for the prompt and timely submittal of all shop and working drawings so that there shall be no delay to the work due to the absence of such drawings.

No material or equipment shall be purchased or fabricated for the contract until the required shop and working drawings have been submitted as herein above provided and approved as conforming to the contract requirements. All such materials and equipment and the work involved in their installation or incorporated into the work shall then be as shown in and represented by said drawings.

Until the necessary approval has been given, the Contractor shall not proceed with any portion of the work such as the construction of foundations, the design or details of which are dependent upon the design or details of work, materials, equipment or other features for which approval is required.

All shop and working drawings shall be submitted to the Engineer by and/or through the Contractor, who shall be responsible for obtaining shop and working drawings from his subcontractors and returning approved drawings to them. Unless otherwise approved, all shop and working drawings shall be prepared on standard size, 24 inch by 36 inch sheets, except those which are made by changing existing standard shop or working drawings. All drawings shall be clearly marked with the names of the Town, Contractor, and building, equipment or structure to which the drawing applies, and shall be accompanied by a letter of transmittal giving a list of the drawing number and the names mentioned above.

Only drawings which have been checked and corrected by the fabricator should be submitted to the Contractor by his subcontractors and vendors. Prior to submitting drawings to the Engineer, the Contractor shall check thoroughly all such drawings to satisfy himself that the subject matter thereof conforms to the drawings and specifications in all respects. All drawings which are correct shall be marked with the date, checker's name and indication of the Contractor's approval, and then shall be submitted to the Engineer. Other drawings shall be returned for correction.

The approval of shop and working drawings, etc., will be general only and shall not relieve or in any respect diminish the responsibility of the Contractor for details of design, dimensions, etc., necessary for proper fitting and construction of the work as required in the contract and for achieving the result and performance specified hereunder.

Should the Contractor submit for approval, equipment that requires modifications to the structures, piping, layout, etc., detailed on the drawings, he shall also submit for approval, details of the proposed modifications. If such equipment and modifications are approved, the Contractor, at no additional cost to the Town, shall do all work necessary to make such modifications.

The marked-up reproducible of the shop and working drawings or one mark-up copy of catalog cuts will be returned to the Contractor. The Contractor shall furnish additional copies of such drawings or catalog cuts when so requested.

57. OCCUPYING PRIVATE LAND:

The Contractor shall not (except after written consent from the proper parties) enter or occupy with men, tools, materials, or equipment, any land outside the right-of-

way or property of the Town. A copy of the written consent shall be given to the Engineer.

58. INTERFERENCE WITH AND PROTECTION OF STREETS:

The Contractor shall not close or obstruct any portion of a street, road or private way without obtaining permits therefore from the proper authorities. If any street, road or private way shall be rendered unsafe by the Contractor's operations, he shall make such repairs or provide such temporary ways or guards as shall be acceptable to the Engineer and to the proper authorities.

Streets, roads, private ways and walks not closed shall be maintained passable and safe by the Contractor, who shall assume and have full responsibility for the adequacy and safety of provisions made therefore.

The Contractor shall, at least 24 hours in advance, notify the Police and Fire Departments in writing, with a copy to the Engineer, if the closure of a street or road is necessary. He shall cooperate with the Police Department in the establishment of alternate routes and shall provide adequate detour signs, plainly marked and well-lighted, in order to minimize confusion.

59. STORAGE OF MATERIALS AND EQUIPMENT:

All excavated materials, construction equipment and materials and equipment to be incorporated in the work shall be placed so as not to injure any part of the work or existing facilities and so that free access can be had at all times to all parts of the work and to all Public Utility installations in the vicinity of the work. Materials and equipment shall be kept neatly piled and compactly stored in such locations as will cause a minimum of inconvenience to public travel and adjoining owners, tenants and occupants.

60. INSUFFICIENCY OF SAFETY PRECAUTIONS:

If at any time, in the sole judgment of the Engineer, the work is not properly lighted, barricaded, or in any other respect safe in regard to public travel, persons on or about the work, or public or private property, the Engineer shall have the right to order such safeguards to be erected and such precautions to be taken as he deems advisable and the

Contractor shall comply promptly with such orders. If, under such circumstances, the Contractor does not or cannot immediately put the work and the safeguards into proper and approved condition, or if the Contractor or his representative is not upon the site so that he can be notified immediately of the insufficiency of safety precautions, the

Engineer may put the work into such a condition that it shall be, in his opinion, in all respects safe. The Contractor shall pay all costs and expenses incurred by the Engineer or Town in so doing. Such action of the Engineer, or his failure to take such action, shall in no way relieve or diminish the responsibility of the Contractor for any and all costs, expenses, losses, liability, claims, suits, proceedings, judgments, awards or damages resulting from, by reason of or in connection with any failure to take safety precautions or the insufficiency of the safety precautions taken by him or by the Engineer acting under authority of this article or for failure to comply with the provisions of any State or Federal Occupational Safety and Health Laws, Rules or Regulations.

61. SANITARY REGULATIONS:

When deemed necessary by the Engineer, the suitable Contractor shall provide sanitary facilities for the use of those employed on the work. Such facilities shall be made available when the first employees arrive on the site of the work, shall be properly secluded from public observation and shall be constructed and maintained during the progress of the work in suitable numbers and at such points and in such manner as may be required or approved.

The Contractor shall maintain the sanitary facilities in a satisfactory and sanitary condition at all times and shall enforce their use. He shall rigorously prohibit the committing of nuisances on the site of the work, on the lands of the Town, or on adjacent property.

The Town and the Engineer shall have the right to inspect such facilities at all times to determine whether or not they are being properly and adequately maintained.

62. DELETE

63. DIMENSIONS OF EXISTING STRUCTURES:

Where the dimensions and locations of existing structures are of importance in the installation or connection of any part of the work, the Contractor shall verify such dimensions and locations in the field before the fabrication of any material or equipment which is dependent on the correctness of such information.

64. WORK TO CONFORM:

During its progress, and on its completion, the work shall conform truly to the lines, levels and grades indicated on the drawings or given by the Engineer and shall be built in a thoroughly substantial and workmanlike manner, in strict accordance with the drawings, specifications and other contract documents and the directions given from time to time by the Engineer.

65. COMPUTATION OF QUANTITIES:

For estimating quantities in which the computation of areas by Geometric methods would be comparatively laborious, it is agreed that the Planimeter shall be

considered an instrument adapted to the measurement of such areas. It is further agreed that the computation of the Volume Prismoids shall be by the method of average end areas.

66. PLANNING AND PROGRESS SCHEDULES:

Before starting the work and from time to time during its progress, as the Engineer may request, the Contractor shall submit to the Engineer a written description of the methods he plans to use in doing the work and the various steps he intends to take.

Within two (2) days after the date of starting work, the Contractor shall prepare and submit to the Engineer a written schedule fixing the respective dates for the start and

completion of various parts of the work. The Contractor shall update the schedule on a monthly basis and submit each schedule to the Engineer for review, approval and change where necessary during the progress of the work.

67. PRECAUTIONS DURING ADVERSE WEATHER:

During adverse weather and against the possibility thereof, the Contractor shall take all necessary precautions so that the work may be properly done and satisfactory in all respects. When required, protection shall be provided by the use of plastic sheets, tarpaulins, wood and building-paper shelters or other approved means.

The Engineer may suspend construction operations at any time when, if in his sole judgment, the conditions are unsuitable or the proper precautions are not being taken, whatever the weather may be.

68. AS-BUILT DRAWINGS:

The Contractor shall be responsible for maintaining a set of as-built drawings during the course of the work for examination by the Engineer.

69. SCOPE OF WORK:

The intent of the contract is to complete the work or improvements in full compliance with the plans, specifications, technical specifications, special notes, etc.

A. Quantities

The unit bid prices shall be applied to the applicable quantities actually used and accepted in the performance of this project. Quantities have been established using the best information available for accuracy. In some instances, however, quantities may have been provided for some items in order to establish a unit price in the eventuality that the item of work may occur during the construction of the project.

Should the actual quantities constructed vary from those estimated, whether higher or lower, the Contractor is made aware that the applicable item will be paid for based upon his unit bid price bid for that item. Exceptions to this article are noted below in section C, Change in Project Scope.

B. Cost Plus Items:

If the Town orders the performance of any work not covered by the drawings or specifications, and for which no unit price or lump sum basis can be agreed upon, then such extra work shall be done on a Cost-Plus percentage basis of payment as follows:

1.0 Direct Labor And Foreman Costs - For all labor including equipment operators, and foremen in direct charge of the specific operation, the Contractor shall receive the rate of wage actually paid as shown by his certified payroll, which shall be at least the current local minimum prevailing wage rate, per hour, per position, in accordance with the current State of Connecticut, Labor Department Minimum Rates & Classifications for Heavy Construction. Compensation shall be for each hour that said labor and foreman are actually engaged in such work, including such overtime as provided by existing laws and regulations. In addition the contractor shall receive for each hour worked, the actual costs

paid to, or in behalf of workmen, by reason of allowances, health and welfare benefits, pension fund benefits or other benefits, when such amounts are required by collective bargaining agreement or other employment contract generally applicable to the classes of labor employed on the work. All personnel above the grade of foreman are excluded from receiving compensation under this section.

An amount equal to 20 percent of the total sums as specified above (1.0) will also be paid the contractor.

1.1 Other Labor Costs - The Contractor shall also be allowed to add to such direct labor and foremen costs, the following items:

Social Security Tax at the percentage legally required; Unemployment Ins., at the percentage legally required; Workmen's Compensation insurance at policy percentage rate; Property/liability damage insurance premiums;

An amount equal to 6 percent of the total sums as specified above (1.1) will also be paid the contractor.

1.2 Materials - For all materials used, the Contractor shall receive the actual cost of such materials, including freight and delivery charges, as shown by original receipted bills to which shall be added a sum equal to fifteen (15) percent.

1.3 Equipment Rental - For machinery, trucks, or equipment, exclusive of operator's hire, and except small tools and equipment for which no rental is allowed, which it may be deemed necessary to use, the Town will allow the Contractor the cost of renting such machinery, trucks, or equipment, which shall include fuel and lubricants, as are actually used in the performance of the work, but to which no percentage shall be added.

Equipment rental costs will be based upon the "Rental Rate Blue Book" including Rate Adjustment Tables and amendments as published by Dataquest, Inc., San Jose, California or a lower rate if so submitted by the Contractor, and must be approved by the Town prior to any work being performed.

1.4 Sub-Contracts - Cost-Plus work may be performed by a subcontractor only when (a) the Contractor has obtained approval of the subcontractor by the Town and (b) the work has been performed by the subcontractor in strict compliance with the terms of the contract. In such event, the Contractor shall receive the cost of any such sub-contract to which shall be added a sum equal to ten (10) percent.

25

1.5 Superintendence - The foregoing payments shall be received by the Contractor as payment in full for all work done on a Cost Plus basis, and shall be accepted to cover all general superintendence, use of small tools and equipment for which no rental is allowed, job and general overhead, bonding, expenses, and anticipated profit.

2.0 The cost of the work done each day shall be submitted to the Engineer in a satisfactory form, on the succeeding day and shall be approved by him or adjusted accordingly.

3.0 Monthly payments of all charges for extra work, whether priced on the Cost Plus basis or an agreed-upon basis, shall upon completion, and approval, be requested with the subsequent monthly progress billing.

C. Change of Project Scope

In the event that the overall scope of the project is increased or decreased by 25% or more, either party to the contract may request a revised contract consideration to the stipulated bid unit prices that may be affected by the change. After agreement is reached by the Town and contractor on revised unit prices, a change order will be issued reflecting these changes. The re-negotiated unit prices will be based on the original contract unit prices with additions or subtractions indicated so as to justify the new unit price to the satisfaction of the Town. The revised unit prices will be applied only to that portion of the project in which the scope has been changed, in accordance with this article, and shall not be applied to any of the quantities of the original bid. An example of such a change may be the addition to or deletion of the originally stated project areas.

All of the above requirements shall be carried out in accordance with the provisions of the Trumbull Code, Article II, Purchasing, Section 23-18.4, Contracts.

70. FIELD OFFICE

Not applicable for this project.

71. COORDINATION OF PLANS/SPECIFICATIONS

Any requirement on the plans or in these Specifications, Special Notes/Provisions shall be equally binding on the Contractor.

In case of conflict, the plans shall take precedence over the Specifications. Special Notes/Provisions shall take precedence over plans and Specifications.

72. NO PAYMENT

Unless otherwise provided for by a specific Contract Item, no separate payment shall be made for any of the requirements as described in the above General Specifications, but shall be deemed included in the total bid price for all the work in this Contract.

73. NOISE

The Contractor will be required to limit noise operations pursuant to Town of Trumbull Charter Chapter 164 -1 to and including Chapter 164 -13

TABLE OF CONTENTS OF SPECIAL PROVISIONS

Note: This Table of Contents has been prepared for the convenience of those using this contract with the sole express purpose of locating quickly the information contained herein; and no claims shall arise due to omissions, additions, deletions, etc., as this Table of Contents shall not be considered part of the contract.

August 2018

**Pequonnock River Trail Crossings
Route 111 at Old Mine Road
Whitney Avenue at Pequonnock River Trail**

Town of Trumbull

The State of Connecticut, Department of Transportation, Standard Specifications for Roads, Bridges, Facilities and Incidental Construction, Form 817, 2016 as revised by Supplemental Specifications dated January 2018 (otherwise collectively as "ConnDOT Form 817"), is hereby made part of this contract, as modified by the Special Provisions contained herein. The current edition of the State of Connecticut Department of Transportation's "Construction Contract Bidding and Award Manual" ("Manual"), is hereby made part of this contract. If the provisions of this Manual conflict with provisions of other Department documents (not including statutes or regulations), the provisions of the Manual will govern. The Manual is available upon request from the Transportation Manager of Contracts.

The Special Provisions relate in particular to the PEQUONNOCK RIVER TRAIL CROSSINGS PROJECT in the Town of Trumbull.

Table of Contents

REQUIRED PROVISIONS

SECTION 1.05	NOTICE TO CONTRACTOR – TRAFFIC SIGNALS
SECTION 1.06	CONTROL OF WORK
SECTION 1.07	CONTROL OF MATERIALS
SECTION 1.08	LEGAL RELATIONS AND RESPONSIBILITIES
SECTION 10.00	PROSECUTION AND PROGRESS
	GENERAL CLAUSES FOR HIGHWAY ILLUMINATION AND TRAFFIC SIGNAL PROJECTS
ITEM# 0865200A	Inlaid Thermoplastic Pavement Marking System Crosswalk
ITEM# 0950191A	Turf Establishment -Lawn
ITEM# 0970006A	Traffic Person (Municipal Police Officer)
ITEM# 0971001A	Maintenance and Protection of Traffic
ITEM# 1027032A	Service (metered)
ITEM# 1107007A	Pedestrian Push Button and Sign (Piezo)
ITEM# 1117110A	Rectangular Rapid Flashing Beacon (RRFB) Type B
ITEM# 1108163A	Modify Existing Controller
ITEM# 1111801A	Removal and/or Relocation of Traffic Signal Equipment
ITEM# 1206023A	Removal and Relocation of Existing Signs
ITEM# 1208931A	Sign Face - sheet Aluminum (Type IX Retroreflective Sheeting)
ITEM# 1800001A	Radar Speed Display Signs- Solar and Battery

NOTICE TO CONTRACTOR - TRAFFIC SIGNALS

The Contractor is hereby notified that certain conditions pertaining to the installation of new signals and maintenance of traffic signal operations are required when relevant, as part of this contract.

Qualified/Unqualified Workers

U.S. Department of Labor

Occupational Safety & Health Administration (OSHA) www.osha.gov

Part Number	1910
Part Title	Occupational Safety & Health Administration
Subpart	S
Subpart Title	Electrical
Standard Number	1910.333
Title	Selection and use of work practices

Completion of this project will require Contractor employees to be near overhead utility lines. All workers and their activities when near utility lines shall comply with the above OSHA regulations. In general, unqualified workers are not allowed within 10 feet of overhead, energized lines. It is the contractor's responsibility to ensure that workers in this area are qualified in accordance with OSHA regulations.

The electric distribution company is responsible to provide and install all necessary anchors and guy strands on utility poles. It is the Contractors responsibility to coordinate with the utility company to ensure proper placement of the anchor.

Utility poles cannot be double loaded without proper guying.

The contractor will be held liable for all damage to existing equipment resulting from his or his subcontractor's actions. A credit will be deducted from monies due the Contractor for all maintenance calls responded to by Department of Transportation personnel.

All existing traffic appurtenances, in particular steel span poles, controller cabinets and pedestals shall be removed from the proposed roadway prior to excavation. The Contractor shall work with the utility companies to either relocate or install all traffic signal appurtenances prior to the roadway reconstruction.

The Contractor must install permanent or temporary spans in conjunction with utility company relocations. He then must either install the new signal equipment and controller or relocate the existing equipment.

The 30 Day Test on traffic control equipment, as specified in Section 10.00, Article 10.00.10 - TESTS, will not begin until the items listed below are delivered to the Town of Trumbull Department of Public Works.

Five (5) sets of cabinet wiring diagrams. Leave one set in the controller cabinet.
All spare load switches and flash relays.

SECTION 1.05 - CONTROL OF THE WORK

Article 1.05.02 - Plans, Working Drawings and Shop Drawings is supplemented as follows:

Subarticle 1.05.02 - (2) is supplemented by the following:

Traffic Signal Items:

When required by the contract documents or when ordered by the Engineer, The Contractor shall prepare and submit product data sheets, working drawings and/or shop drawings for all traffic signal items to the Town of Trumbull and Engineer for approval before fabrication. The packaged set of product data sheets, working drawings and/or shop drawings shall be submitted either in paper (hard copy) form or in an electronic portable document format (.pdf). The package submitted in paper form shall include one (1) set. Product data sheets shall be printed on ANSI A (8 1/2" x 11"; 216 mm x 279mm; letter) sheets. Working drawings and shop drawings shall be printed on ANSI B (11" x 17"; 279 mm x 432 mm; ledger/tabloid) sheets.

Please send the documents via mail to:

Frank Smeriglio, P.E.
Engineering Department
5886 Main Street
Trumbull, CT 06611

The packaged set submitted in an electronic portable document format (.pdf) shall be in an individual file with appropriate bookmarks for each item. The electronic files for product data sheets shall be created on ANSI A (8 1/2" x 11"; 216 mm x 279mm; letter) sheets. Working drawings and shop drawings shall be created on ANSI B (11" x 17"; 279 mm x 432 mm; ledger/tabloid) sheets.

Please send the pdf documents via email to:

fsmeriglio@trumbull-ct.gov

A copy of the approved equipment shall be sent to the Division of Traffic Engineering - Electrical in pdf format via email to:

DOT.TrafficElectrical@ct.gov

SECTION 1.06 CONTROL OF MATERIALS

Article 1.06.01 - Source of Supply and Quality:

Add the following:

Traffic Signal Items:

For the following traffic signal items the contractor shall submit a complete description of the item, working drawings, product data sheets and other descriptive literature which completely illustrates such items presented for formal approval. Such approval shall not change the requirements for a certified test report and materials certificate as may be called for. All documents shall be submitted at one time, unless otherwise approved by the engineer.

Aluminum Pedestals
Rigid Metal Conduit
Pedestrian Pushbuttons and Type of Sign
Rectangular Rapid Flashing Beacon

SECTION 1.06 CONTROL OF MATERIALS

Article 1.06.07 - Certified Test Reports and Materials Certificate.

Add the following:

- 1) For the materials in the following traffic signal items, a Certified Test Report will be required confirming their conformance to the requirements set forth in these plans or specifications or both. Should the consignee noted on a Certified Test Report be other than the Prime Contractor, then Materials Certificates shall be required to identify the shipment.

- 2) For the materials in the following traffic signal items, a Materials Certificate will be required confirming their conformance to the requirements set forth in these plans or specifications or both.

Concrete Handhole
Aluminum Pedestals

SECTION 1.07 - LEGAL RELATIONS AND RESPONSIBILITIES

Article 1.07.13 - Contractor's Responsibility for Adjacent Property, Facilities and Services is supplemented as follows:

The following company and representative shall be contacted by the Contractor to coordinate the protection of their utilities on this project 30 days prior to the start of any work on this project involving their utilities:

Mr. Gerard McDonald
District 3 Electrical Supervisor
Department of Transportation
Milford, Connecticut
(203) 882-2033

Mr. Keith Cournoyer
Construction Supervisor
Charter Communications Entertainment I, LLC
North Windham, CT 06256
(860) 456-8346

Ms. Jan Possidente – Russo
Manager – Conduit
Frontier Communications
Meriden, CT 06450
(203) 383-6645

Mr. Terry Shea
Lightower Fiber Networks
Cheshire, CT 06410
(203) 649-3905

Mr. Jacob Musto
Field Service Technician
United Illuminating
New Haven, CT 06510
(203) 499-2687

SECTION 1.08 - PROSECUTION AND PROGRESS

Article 1.08.04 - Limitation of Operations - Add the following:

In order to provide for traffic operations as outlined in the Special Provision "Maintenance and Protection of Traffic," the Contractor will not be permitted to perform any work which will interfere with the described traffic operations on all project roadways as follows:

Route 111

On the following State observed Legal Holidays:

New Year's Day
Good Friday, Easter*
Memorial Day
Independence Day
Labor Day
Thanksgiving Day**
Christmas Day

The following restrictions also apply:

On the day before and the day after any of the above Legal Holidays.

On the Friday, Saturday, and Sunday immediately preceding any of the above Holidays celebrated on a Monday.

On the Saturday, Sunday, and Monday immediately following any of the above Holidays celebrated on a Friday.

* From 6:00 a.m. the Thursday before the Holiday to 8:00 p.m. the Monday after the Holiday.

** From 6:00 a.m. the Wednesday before the Holiday to 8:00 p.m. the Monday after the Holiday.

Route 111 and Old Mine Road

Monday through Friday between 6:00 a.m. and 8:30 a.m. & between 4:00 p.m. and 6:00 p.m.
Saturday and Sunday between 10:00 a.m. and 6:00 p.m.

All Other Roadways

Monday through Friday between 6:00 a.m. and 9:00 a.m. & between 3:00 p.m. and 6:00 p.m.
Saturday and Sunday between 10:00 a.m. and 6:00 p.m.

Additional Lane Closure Restrictions

It is anticipated that work on adjacent projects will be ongoing simultaneously with this project. The Contractor shall be aware of those projects and anticipate that coordination will be required to maintain proper traffic flow at all times on all project roadways, in a manner consistent with these specifications and acceptable to the Engineer.

The Contractor will not be allowed to perform any work that will interfere with traffic operations on a roadway when traffic operations are being restricted on that same roadway, unless there is at least a one mile clear area length where the entire roadway is open to traffic or the closures have been coordinated and are acceptable to the Engineer. The one mile clear area length shall be measured from the end of the first work area to the beginning of the signing pattern for the next work area.

SECTION 10.00 - GENERAL CLAUSES FOR HIGHWAY ILLUMINATION AND TRAFFIC SIGNAL PROJECTS

Article 10.00.10 Section 3. Functional Inspection, first paragraph after the 2nd sentence: Add the following:

The contractor shall have a bucket truck with crew on site during the Functional Inspection to make any necessary aerial signal adjustments as directed by the Engineer.

Article 10.00.12 - Negotiations with utility company: Add the following:

The contractor shall give notice to utility companies a minimum of 30 days prior to required work or services to the utility company. Refer to Section 1.07 – Legal Relations and Responsibilities for the list of utility companies and representatives the contractor shall use.

The Contractor shall perform all work in conformance with Rules and Regulations of Public Utility Regulatory Authority (PURA) concerning Traffic Signals attached to Public Service Company Poles. The Contractor is cautioned that there may be energized wires in the vicinity of the specified installations. In addition to ensuring compliance with NESC and OSHA regulations, the Contractor and/or its Sub-Contractors shall coordinate with the appropriate utility company for securing/protecting the site during the installation of traffic signal mast arms, span poles or illumination poles.

When a span is attached to a utility pole, the Contractor shall ensure the anchor is in line with the proposed traffic signal span wire. More than 5 degree deviation will lower the holding strength and is not allowed. The Contractor shall provide any necessary assistance required by the utility company, and ensure the anchor and guy have been installed and properly tensioned prior to attaching the span wire to the utility pole.

ITEM#0865200A INLAID THERMOPLASTIC PAVEMENT MARKING SYSTEM CROSSWALK

Description:

The work under this Item shall include the installation of inlaid thermoplastic pavement marking system crosswalk where shown on the plans or as directed by the Engineer.

Materials:

The thermoplastic resin imprint material shall conform to the following:

Grade	45 (Light/Med Traffic)	60 (Heavy Traffic)
Average Temp. Range	25 - 113 degrees F	25 - 140 degrees F
Wheel Tracking @ 113 F	less than 1 mm/hr	less than 1 mm/ hr
Wheel Tracking @ 140 F	N/A	less than 5 mm/hr
Density	2.12	2.12
Cone Flow Test (5 hrs. @ 194 F)	15% maximum	15% maximum
Plane Test (5 hrs. @ 194 F)	5% maximum	5% maximum
Indent @ 104 F	25 dmm maximum	50 dmm maximum
Indent @ 122 F	N/A	75 dmm maximum
Ash Content	90% maximum	90% maximum
Skid Resistance Value	55 - 70	55 - 70

Preparation:

In full-depth reconstruction areas, the width of the sidewalk to receive the thermoplastic resin application shall be paved to within 3/4 inches of the finished pavement surface.

Sawcutting shall be incidental to this item.

The Contractor shall maintain a minimum ten-foot travel lane at all times during this operation.

The Contractor shall prepare the area to receive the resin application according to the resin manufacturer and will not be allowed to proceed with the resin application until the area has been inspected by the resin manufacturer and the Engineer.

Construction Method:

The Contractor shall be responsible for the preparation, placement and patterning of the thermoplastic resin according to the manufacturer and subject to the approval of the Engineer. This synthetic paving material shall be composed of a hot-applied, resin-based compound formulated with a color stable pigment throughout that shall be surface textured to simulate hand laid brick, cobble, stone and/or masonry. The contractor will be required to overlay imprint in

previously prepared recessed pavement surfaces as described in the excavation section and/or other areas, as directed and approved by the Engineer.

The Contractor must be a manufacturer authorized applicator, experienced with this specialized system subject to approval by the Town of Trumbull.

This work shall be performed as follows:

1. Using manufacturer prescribed methods and equipment, the Contractor shall adequately heat and uniformly mix the imprint material(s) together. The Town will select the resin color(s) from the available pigments supplied by the manufacturer. Maximum heating temperature of the completed formulation is 440 degrees Fahrenheit.
2. The Contractor shall then apply the heated, mixed resin material to the surface of a hardened, structurally sound bituminous concrete or cement concrete pavement, as directed by the Engineer. The resin material shall be spread to the desired thickness (3/4 inches) using specialized ironing tools, heated sufficiently to smooth the surface to a state of readiness for texturizing. **No material shall be applied when precipitation is present or if the pavement surface is wet.**
3. The color and surface pattern shall be in accordance with the design approved by the Town (red brick in pedestrian areas and gray cobble in vehicular areas). Texturizing will begin immediately after leveling has occurred, while the material is still hot enough to allow the mold selected, to adequately penetrate the surface and create the desired pattern or form. The resin surface pattern in pedestrian areas shall be generally planar and smooth so as to not interfere with rollability and smoothness of walking surface.
4. Once the finished surface has cooled sufficiently, the application area may be opened to vehicular and/or pedestrian traffic.
5. Any residue resulting from this work shall be removed and disposed of according to Item 120.1 Unclassified Excavation contained herein. The completed work area is to be left in a neat and clean condition.

The resin shall conform to the minimum following physical and performance properties: hot-applied resin-based compound developed specifically for use on bituminous or cement concrete, with superior adhesion, flexibility and abrasion resistance characteristics, as well as color stability, chemical resistance and scrub ability.

The Contractor shall take all precautions and steps during the resin application process to prevent bodily harm or injury, damage to adjacent materials such as new curb, sidewalks, drainage structures or water supply facilities. If during the execution of the work, the Contractor, through willfulness or carelessness, permits or causes any damage to public or private property, the cost of repair or replacement shall be the responsibility of the Contractor at no cost to the Town.

The Contractor will be required to own or have access to the required specialized machinery and equipment necessary to perform this work, including but not limited to specialized trucks, compressor, miscellaneous asphalt equipment, dispensers, applicators, cutters and/or specialized tools, etc.

Method of Measurements:

Inlaid Thermoplastic Pavement Marking System Crosswalk will be measured for payment by the square yard on the pavement surface complete in place.

Basis of Payment:

This work will be paid for at the contract unit price per square yard of "Inlaid Thermoplastic Pavement Marking System Crosswalk" which price shall include all labor, materials, equipment, and incidental costs required to complete the work including asphalt emulsion.

Pay Item	Pay Unit
Inlaid Thermoplastic Pavement Marking System Crosswalk	s.y.

ITEM #0950019A - TURF ESTABLISHMENT - LAWN

Description: The work included in this item shall consist of providing an accepted stand of grass by furnishing and placing seed as shown on the plans or as directed by the Engineer.

Materials: The materials for this work shall conform to the requirements of Section 9.50 of Standard Specification Form 817. The following mix shall be used for this item:

Turf Seed Mix:

In order to preserve and enhance the diversity, the source for seed mixtures shall be locally obtained within the Northeast USA including New England, New York, Pennsylvania, New Jersey, Delaware, or Maryland. One approved seed mixture is detailed below. Other proposed mixtures must be approved by the Conn DOT Landscape Design office.

Proportion (Percent)	Species Common name	Scientific name
25	Abbey Kentucky Bluegrass	Poa pratensis
15	Envicta Kentucky Bluegrass	Poa pratensis
25	Pennlawn Red Fescue	Festuca rubra
15	Ambrose Chewing Fescue	Festuca rubra
20	Manhattan Ryegrass	Lolium perenne

Fertilizer:

Fertilizer shall be Starter fertilizer.

Mulch:

Mulch shall be Mulch Master shredded hay. Salt hay or straw hay shall not be permitted.

Construction Methods: Construction Methods shall be those established as agronomically acceptable and feasible and that are approved by the Engineer. Rate of application shall be field determined in Pure Live Seed (PLS) based on the minimum purity and minimum germination of the seed obtained. Calculate the PLS for each seed species in the mix. Adjust the seeding rate for the above composite mix, based on 250 lbs. (274 kg.) per acre (hectare). The seed shall be mulched in accordance with Article 9.50.03.

Method of Measurement: This work will be measured for payment by the number of square yards (square meters) of surface area of accepted established grasses as specified or by the number of square yards (square meters) of surface area of seeding covered and as specified.

Basis of Payment: This work will be paid for at the contract unit price per square yard (square meters) for "Turf Establishment - Lawn" which price shall include all materials maintenance, equipment, tools, labor, and work incidental thereto. Partial payment of up to 60% may be made for work completed, but not accepted.

Pay Item
Turf Establishment -Lawn

Pay Unit
S.Y.

ITEM #0970006A - TRAFFICPERSON (MUNICIPAL POLICE OFFICER)

Description: Under this item the Contractor shall provide the services of Trafficpersons of the type and number, and for such periods, as the Engineer approves for the control and direction of vehicular traffic and pedestrians. Traffic persons requested solely for the contractor's operational needs will not be approved for payment.

Construction Method: Prior to the start of operations on the project requiring the use of Trafficpersons, a meeting will be held with the Contractor, Trafficperson agency or firm, Engineer, and State Police, if applicable, to review the Trafficperson operations, lines of responsibility, and operating guidelines which will be used on the project. A copy of the municipal it y's billing rates for Municipal Police Officers and vehicles, if applicable, will be provided to the Engineer prior to start of work.

On a weekly basis, the Contractor shall inform the Engineer of their scheduled operations for the following week and the number of Trafficpersons requested. The Engineer shall review this schedule and approve the type and number of Trafficpersons required. In the event of an unplanned, emergency, or short-term operation, the Engineer may approve the temporary use of properly clothed persons for traffic control until an authorized Trafficperson may be obtained. In no case shall this temporary use exceed 8 hours for any operation.

If the Contractor changes or cancels any scheduled operations without prior notice of same as required by the agency providing the Trafficpersons, and such that Trafficperson services are no longer required, the Contractor will be responsible for payment at no cost to the Department of any show-up cost for any Trafficperson not used because of the change. Exceptions, as approved by the Engineer, may be granted for adverse weather conditions and unforeseeable causes beyond the control and without the fault or negligence of the Contractor.

Trafficpersons assigned to a work site are to only take direction from the Engineer.

Trafficpersons shall wear a high visibility safety garment that complies with OSHA, MUTCD, ASTM Standards and the safety garment shall have the words "Traffic Control" clearly visible on the front and rear panels (minimum letter size 2 inches (50 millimeters). Worn/faded safety garments that are no longer highly visible shall not be used. The Engineer shall direct the replacement of any worn/faded garment at no cost to the State.

A Trafficperson shall assist in implementing the traffic control specified in the Maintenance and Protection of Traffic contained elsewhere in these specifications or as directed by the Engineer. Any situation requiring a Trafficperson to operate in a manner contrary to the Maintenance and Protection of Traffic specification shall be authorized in writing by the Engineer.

Trafficpersons shall consist of the following types:

1. Uniformed Law Enforcement Personnel: Law enforcement personnel shall wear the high visibility safety garment provided by their law enforcement agency. If no high visibility safety garment is provided, the Contractor shall provide the law enforcement personnel with a garment meeting the requirements stated for the Uniformed Flaggers' garment.

Law Enforcement Personnel may be also be used to conduct motor vehicle enforcement operations in and around work areas as directed and approved by the Engineer.

Municipal Police Officers: Uniformed Municipal Police Officers shall be sworn Municipal Police Officers or Uniformed Constables who perform criminal law enforcement duties from the Municipality in which the project is located. Their services will also include an official Municipal Police vehicle when requested by the Engineer. Uniformed Municipal Police Officers will be used on non-limited access highways. If Uniformed Municipal Police Officers are unavailable, other Trafficpersons may be used when authorized in writing by the Engineer.

Uniformed Municipal Police Officers and requested Municipal Police vehicles will be used at such locations and for such periods as the Engineer deems necessary to control traffic operations and promote increased safety to motorists through the construction sites.

Method of Measurement: Services of Trafficpersons will be measured for payment by the actual number of hours for each person rendering services approved by the Engineer. These services shall include, however, only such trafficpersons as are employed within the limits of construction, project right of way of the project or along detours authorized by the Engineer to assist the motoring public through the construction work zone. Services for continued use of a detour or bypass beyond the limitations approved by the Engineer, for movement of construction vehicles and equipment, or at locations where traffic is unnecessarily restricted by the Contractor's method of operation, will not be measured for payment.

Trafficpersons shall not work more than twelve hours in any one 24-hour period. In case such services are required for more than twelve hours, additional Trafficpersons shall be furnished and measured for payment.

Travel time will not be measured for payment for services provided by Uniformed Municipal Police Officers.

Mileage fees associated with Trafficperson services will not be measured for payment.

Safety garments and STOP/SLOW paddles will not be measured for payment.

Basis of Payment: Trafficpersons will be paid in accordance with the schedule described herein. There will be no direct payment for safety garments or STOP/SLOW paddles. All costs associated with furnishing safety garments and STOP/SLOW paddles shall be considered included in the general cost of the item.

1. Uniformed Law Enforcement Personnel: The sum of money shown on the Estimate and in the itemized proposal as "Estimated Cost" for this work will be considered the bid price even though payment will be made as described below. The estimated cost figure is not to be altered in any manner by the bidder. Should the bidder alter the amount shown, the altered figures will be disregarded and the original price will be used to determine the total amount for the contract.

The Department will pay the Contractor its actual costs for " Trafficperson (Municipal Police Officer)" plus an additional 5% as reimbursement for the Contractor's administrative expense in connection with the services provided.

The invoice must include a breakdown of each officer's actual hours of work and actual rate applied. Mileage fees associated with Trafficperson services are not reimbursable expenses and are not to be included in the billing invoice. The use of a municipal police vehicle authorized by the Engineer will be paid at the actual rate charged by the municipality. Upon receipt of the invoice from the municipality, the Contractor shall forward a copy to the Engineer. The invoice will be reviewed and approved by the Engineer prior to any payments. *Eighty (80%) of the invoice will be paid upon completion of review and approval. The balance (20%) will be paid upon receipt of cancelled check or receipted invoice, as proof of payment.* The rate charged by the municipality for use of a uniformed municipal police officer and/or a municipal police vehicle shall not be greater than the rate it normally charges others for similar services.

Pay Item
Trafficperson (Municipal Police Officer)

Pay Unit
Est.

ITEM NO. 0971001A – MAINTENANCE AND PROTECTION OF TRAFFIC

Article 9.71.01 – Description is supplemented by the following:

The Contractor shall maintain and protect traffic as described by the following and as limited in the Special Provision "Prosecution and Progress":

All Roadways

The Contractor shall maintain and protect a minimum of one lane of traffic in each direction, each lane on a paved travel path not less than 11 feet in width.

Excepted therefrom will be those periods, during the allowable periods, when the Contractor is actively working, at which time the Contractor shall maintain and protect at least an alternating one-way traffic operation, on a paved travel path not less than 11 feet in width. The length of the alternating one-way traffic operation shall not exceed 300 feet and there shall be no more than one alternating one-way traffic operation within the project limits without prior approval of the Engineer.

Commercial & Residential Driveways

The Contractor shall maintain access to and egress from all commercial and residential driveways throughout the project limits. The Contractor will be allowed to close said driveways to perform the required work during those periods when the businesses are closed, unless permission is granted from the business owner to close the driveway during business hours. If a temporary closure of a residential driveway is necessary, the Contractor shall coordinate with the owner to determine the time period of the closure.

Article 9.71.03 - Construction Method is supplemented as follows:

General

Unpaved travel paths will only be permitted for areas requiring full depth and full width reconstruction, in which case, the Contractor will be allowed to maintain traffic on processed aggregate for a duration not to exceed 10 calendar days. The unpaved section shall be the full width of the road and perpendicular to the travel lanes. Opposing traffic lane dividers shall be used as a centerline.

The Contractor is required to delineate any raised structures within the travel lanes, so that the structures are visible day and night, unless there are specific contract plans and provisions to temporarily lower these structures prior to the completion of work.

The Contractor shall schedule operations so that pavement removal and roadway resurfacing shall be completed full width across a roadway (bridge) section by the end of a workday (work night), or as directed by the Engineer.

When the installation of all intermediate courses of bituminous concrete pavement is completed for the entire roadway, the Contractor shall install the final course of bituminous concrete pavement.

When the Contractor is excavating adjacent to the roadway, the Contractor shall provide a 3-foot shoulder between the work area and travel lanes, with traffic drums spaced every 50 feet. At the end of the workday, if the vertical drop-off exceeds 3 inches, the Contractor shall provide a temporary traversable slope of 4:1 or flatter that is acceptable to the Engineer.

The Contractor, during the course of active construction work on overhead signs and structures, shall close the lanes directly below the work area for the entire length of time overhead work is being undertaken. At no time shall an overhead sign be left partially removed or installed.

If applicable, when an existing sign is removed, it shall be either relocated or replaced by a new sign during the same working day.

The Contractor shall not store any material on-site which would present a safety hazard to motorists or pedestrians (e.g. fixed object or obstruct sight lines).

The field installation of a signing pattern shall constitute interference with existing traffic operations and shall not be allowed, except during the allowable periods.

Construction vehicles entering travel lanes at speeds less than the posted speed are interfering with traffic, and shall not be allowed without a lane closure. The lane closure shall be of sufficient length to allow vehicles to enter or exit the work area at posted speeds, in order to merge with existing traffic.

Existing Signing

The Contractor shall maintain all existing signs throughout the project limits during the duration of the project. The Contractor shall temporarily relocate signs and sign supports as many times as deemed necessary, and install temporary sign supports if necessary and as directed by the Engineer.

Requirements for Winter

The Contractor shall schedule a meeting with representatives from the Department including the offices of Maintenance and Traffic, and the Town/City to determine what interim traffic control measures the Contractor shall accomplish for the winter to provide safety to the motorists and permit adequate snow removal procedures. This meeting shall be held prior to October 31 of each year and will include, but not be limited to, discussion of the status and schedule of the following items: lane and shoulder widths, pavement restoration, traffic signal work, pavement markings, and signing.

Signing Patterns

The Contractor shall erect and maintain all signing patterns in accordance with the traffic control plans contained herein. Proper distances between advance warning signs and proper taper lengths are mandatory.

Pavement Markings -Non-Limited Access Multilane Roadways

Secondary and Local Roadways

During construction, the Contractor shall maintain all pavement markings on paved surfaces on all roadways throughout the limits of the project.

Interim Pavement Markings

The Contractor shall install painted pavement markings, which shall include centerlines, shoulder edge lines, lane lines (broken lines), lane-use arrows, and stop bars, on each intermediate course of bituminous concrete pavement and on any milled surface by the end of the work day/night. If the next course of bituminous concrete pavement will be placed within seven days, shoulder edge lines are not required. The painted pavement markings will be paid under the appropriate items.

If the Contractor will install another course of bituminous concrete pavement within 24 hours, the Contractor may install Temporary Plastic Pavement Marking Tape in place of the painted pavement markings by the end of the work day/night. These temporary pavement markings shall include centerlines, lane lines (broken lines) and stop bars; shoulder edge lines are not required. Centerlines shall consist of two 4 inch wide yellow markings, 2 feet in length, side by side, 4 to 6 inches apart, at 40-foot intervals. No passing zones should be posted with signs in those areas where the final centerlines have not been established on two-way roadways. Stop bars may consist of two 6 inch wide white markings or three 4 inch wide white markings placed side by side. The Contractor shall remove and dispose of the Temporary Plastic Pavement Marking Tape when another course of bituminous concrete pavement is installed. The cost of furnishing, installing and removing the Temporary Plastic Pavement Marking Tape shall be at the Contractor's expense.

If an intermediate course of bituminous concrete pavement will be exposed throughout the winter, then Epoxy Resin Pavement Markings should be installed unless directed otherwise by the Engineer.

Final Pavement Markings

The Contractor should install painted pavement markings on the final course of bituminous concrete pavement by the end of the work day/night. If the painted pavement markings are not installed by the end of the work day/night, then Temporary Plastic Pavement Marking Tape shall be installed as described above and the painted pavement markings shall be installed by the end of the work day/night on Friday of that week.

If Temporary Plastic Pavement Marking Tape is installed, the Contractor shall remove and dispose of these markings when the painted pavement markings are installed. The cost of furnishing, installing and removing the Temporary Plastic Pavement Marking Tape shall be at the Contractor's expense.

The Contractor shall install permanent Epoxy Resin Pavement Markings in accordance with Section 12.10 entitled "Epoxy Resin Pavement Markings, Symbols, and Legends" after such time as determined by the Engineer.

TRAFFIC CONTROL DURING CONSTRUCTION OPERATIONS

The following guidelines shall assist field personnel in determining when and what type of traffic control patterns to use for various situations. These guidelines shall provide for the safe and efficient movement of traffic through work zones and enhance the safety of work forces in the work area.

TRAFFIC CONTROL PATTERNS

Traffic control patterns shall be used when a work operation requires that all or part of any vehicle or work area protrudes onto any part of a travel lane or shoulder. For each situation, the installation of traffic control devices shall be based on the following:

Speed and volume of traffic
Duration of operation
Exposure to hazards

Traffic control patterns shall be uniform, neat and orderly so as to command respect from the motorist.

In the case of a horizontal or vertical sight restriction in advance of the work area, the traffic control pattern shall be extended to provide adequate sight distance for approaching traffic.

If a lane reduction taper is required to shift traffic, the entire length of the taper should be installed on a tangent section of roadway so that the entire taper area can be seen by the motorist.

Any existing signs that are in conflict with the traffic control patterns shall be removed, covered, or turned so that they are not readable by oncoming traffic.

When installing a traffic control pattern, a Buffer Area should be provided and this area shall be free of equipment, workers, materials and parked vehicles.

Typical traffic control plans 19 through 25 may be used for moving operations such as line striping, pot hole patching, mowing, or sweeping when it is necessary for equipment to occupy a travel lane.

Traffic control patterns will not be required when vehicles are on an emergency patrol type activity or when a short duration stop is made and the equipment can be contained within the shoulder. Flashing lights and appropriate trafficperson shall be used when required.

Although each situation must be dealt with individually, conformity with the typical traffic control plans contained herein is required. In a situation not adequately covered by the typical traffic control plans, the Contractor must contact the Engineer for assistance prior to setting up a traffic control pattern.

PLACEMENT OF SIGNS

Signs must be placed in such a position to allow motorists the opportunity to reduce their speed prior to the work area. Signs shall be installed on the same side of the roadway as the work area. On multi-lane divided highways, advance warning signs shall be installed on both sides of the highway. On directional roadways (on-ramps, off-ramps, one-way roads), where the sight distance to signs is restricted, these signs should be installed on both sides of the roadway.

ALLOWABLE ADJUSTMENT OF SIGNS AND DEVICES SHOWN ON THE TRAFFIC CONTROL PLANS

The traffic control plans contained herein show the location and spacing of signs and devices under ideal conditions. Signs and devices should be installed as shown on these plans whenever possible.

The proper application of the traffic control plans and installation of traffic control devices depends on actual field conditions.

Adjustments to the traffic control plans shall be made only at the direction of the Engineer to improve the visibility of the signs and devices and to better control traffic operations. Adjustments to the traffic control plans shall be based on safety of work forces and motorists, abutting property requirements, driveways, side roads, and the vertical and horizontal curvature of the roadway.

The Engineer may require that the traffic control pattern be located significantly in advance of the work area to provide better sight line to the signing and safer traffic operations through the work zone.

Table I indicates the minimum taper length required for a lane closure based on the posted speed limit of the roadway. These taper lengths shall only be used when the recommended taper lengths shown on the traffic control plans cannot be achieved.

TABLE I – MINIMUM TAPER LENGTHS

POSTED SPEED LIMIT MILES PER HOUR	MINIMUM TAPER LENGTH IN FEET FOR A SINGLE LANE CLOSURE
30 OR LESS	180
35	250
40	320
45	540
50	600
55	660
65	780

SECTION 1. WORK ZONE SAFETY MEETINGS

1.a) Prior to the commencement of work, a work zone safety meeting will be conducted with representatives of DOT Construction, Connecticut State Police (Local Barracks), Municipal Police, the Contractor (Project Superintendent) and the Traffic Control Subcontractor (if different than the prime Contractor) to review the traffic operations, lines of responsibility, and operating guidelines which will be used on the project. Other work zone safety meetings during the course of the project should be scheduled as needed.

1.b) A Work Zone Safety Meeting Agenda shall be developed and used at the meeting to outline the anticipated traffic control issues during the construction of this project. Any issues that can't be resolved at these meetings will be brought to the attention of the District Engineer and the Office of Construction. The agenda should include:

- Review Project scope of work and time
- Review Section 1.08, Prosecution and Progress
- Review Section 9.70, Trafficpersons
- Review Section 9.71, Maintenance and Protection of Traffic
- Review Contractor's schedule and method of operations.
- Review areas of special concern: ramps, turning roadways, medians, lane drops, etc.
- Open discussion of work zone questions and issues
- Discussion of review and approval process for changes in contract requirements as they relate to work zone areas

SECTION 2. GENERAL

2.a) If the required minimum number of signs and equipment (i.e. one High Mounted Internally Illuminated Flashing Arrow for each lane closed, two TMAs, Changeable Message Sign, etc.) are not available; the traffic control pattern shall not be installed.

2.b) The Contractor shall have back-up equipment (TMAs, High Mounted Internally Illuminated Flashing Arrow, Changeable Message Sign, construction signs, cones/drums, etc.) available at all times in case of mechanical failures, etc. The only exception to this is in the case of sudden equipment breakdowns in which the pattern may be installed but the Contractor must provide replacement equipment within 24 hours.

2.c) Failure of the Contractor to have the required minimum number of signs, personnel and equipment, which results in the pattern not being installed, shall not be a reason for a time extension or claim for loss time.

2.d) In cases of legitimate differences of opinion between the Contractor and the Inspection staff, the Inspection staff shall err on the side of safety. The matter shall be brought to the District Office for resolution immediately or, in the case of work after regular business hours, on the next business day.

SECTION 3. INSTALLING AND REMOVING TRAFFIC CONTROL PATTERNS

3.a) Lane Closures shall be installed beginning with the advanced warning signs and proceeding forward toward the work area.

3.b) Lane Closures shall be removed in the reverse order, beginning at the work area, or end of the traffic control pattern, and proceeding back toward the advanced warning signs.

3.c) Stopping traffic may be allowed:

- As per the contract for such activities as blasting, steel erection, etc.
- During paving, milling operations, etc. where, in the middle of the operation, it is necessary to flip the pattern to complete the operation on the other half of the roadway and traffic should not travel across the longitudinal joint or difference in roadway elevation.
- To move slow moving equipment across live traffic lanes into the work area.

3.d) Under certain situations when the safety of the traveling public and/or that of the workers may be compromised due to conditions such as traffic volume, speed, roadside obstructions, or sight line deficiencies, as determined by the Engineer and/or State Police, traffic may be briefly impeded while installing and/or removing the advanced warning signs and the first ten traffic cones/drums only. Appropriate measures shall be taken to safely slow traffic. If required, traffic slowing techniques may be used and shall include the use of Truck Mounted Impact Attenuators (TMAs) as appropriate, for a minimum of one mile in advance of the pattern starting point. Once the advanced warning signs and the first ten traffic cones/drums are installed/removed, the TMAs and sign crew shall continue to install/remove the pattern as described in Section 4c and traffic shall be allowed to resume their normal travel.

3.e) The Contractor must adhere to using the proper signs, placing the signs correctly, and ensuring the proper spacing of signs.

3.f) Additional devices are required on entrance ramps, exit ramps, and intersecting roads to warn and/or move traffic into the proper travelpath prior to merging/exiting with/from the main line traffic. This shall be completed before installing the mainline pattern past the ramp or intersecting roadway.

3.g) Prior to installing a pattern, any conflicting existing signs shall be covered with an opaque material. Once the pattern is removed, the existing signs shall be uncovered.

3.h) On limited access roadways, workers are prohibited from crossing the travel lanes to install and remove signs or other devices on the opposite side of the roadway. Any signs or devices on the opposite side of the roadway shall be installed and removed separately.

SECTION 4. USE OF HIGH MOUNTED INTERNALLY ILLUMINATED FLASHING ARROW

- 4.a) On limited access roadways, one Flashing Arrow shall be used for each lane that is closed. The Flashing Arrow shall be installed concurrently with the installation of the traffic control pattern and its placement shall be as shown on the traffic control plan. For multiple lane closures, one Flashing Arrow is required for each lane closed. If conditions warrant, additional Flashing Arrows should be employed (i.e.: curves, major ramps, etc.).
- 4.b) On non-limited access roadways, the use of a Flashing Arrow for lane closures is optional. The roadway geometry, sight line distance, and traffic volume should be considered in the decision to use the Flashing Arrow.
- 4.c) The Flashing Arrow shall not be used on two lane, two-way roadways for temporary alternating one-way traffic operations.
- 4.d) The Flashing Arrow board display shall be in the “arrow” mode for lane closure tapers and in the “caution” mode (four corners) for shoulder work, blocking the shoulder, or roadside work near the shoulder. The Flashing Arrow shall be in the “caution” mode when it is positioned in the closed lane.
- 4.e) The Flashing Arrow shall not be used on a multi-lane roadway to laterally shift all lanes of traffic, because unnecessary lane changing may result.

SECTION 5. USE OF TRUCK MOUNTED IMPACT ATTENUATOR VEHICLES (TMAs)

- 5.a) For lane closures on limited access roadways, a minimum of two TMAs shall be used to install and remove traffic control patterns. If two TMAs are not available, the pattern shall not be installed.
- 5.b) On non-limited access roadways, the use of TMAs to install and remove patterns closing a lane(s) is optional. The roadway geometry, sight line distance, and traffic volume should be considered in the decision to utilize the TMAs.
- 5.c) Generally, to establish the advance and transition signing, one TMA shall be placed on the shoulder and the second TMA shall be approximately 1,000 feet ahead blocking the lane. The flashing arrow board mounted on the TMA should be in the “flashing arrow” mode when taking the lane. The sign truck and workers should be immediately ahead of the second TMA. In no case shall the TMA be used as the sign truck or a work truck. Once the transition is in place, the TMAs shall travel in the closed lane until all Changeable Message Signs, signs, Flashing Arrows, and cones/drums are installed. The flashing arrow board mounted on the TMA should be in the “caution” mode when traveling in the closed lane.

5.d) A TMA shall be placed prior to the first work area in the pattern. If there are multiple work areas within the same pattern, then additional TMAs shall be positioned at each additional work area as needed. The flashing arrow board mounted on the TMA should be in the “caution” mode when in the closed lane.

5.e) TMAs shall be positioned a sufficient distance prior to the workers or equipment being protected to allow for appropriate vehicle roll-ahead in the event that the TMA is hit, but not so far that an errant vehicle could travel around the TMA and into the work area. For additional placement and use details, refer to the specification entitled “Type ‘D’ Portable Impact Attenuation System”. Some operations, such as paving and concrete repairs, do not allow for placement of the TMA(s) within the specified distances. In these situations, the TMA(s) should be placed at the beginning of the work area and shall be advanced as the paving or concrete operations proceed.

5.f) TMAs should be paid in accordance with how the unit is utilized. When it is used as a TMA and is in the proper location as specified, and then it should be paid at the specified hourly rate for “Type ‘D’ Portable Impact Attenuation System”. When the TMA is used as a Flashing Arrow, it should be paid at the daily rate for “High Mounted Internally Illuminated Flashing Arrow”. If a TMA is used to install and remove a pattern and then is used as a Flashing Arrow, the unit should be paid as a “Type ‘D’ Portable Impact Attenuation System” for the hours used to install and remove the pattern, typically 2 hours (1 hour to install and 1 hour to remove), and is also paid for the day as a “High Mounted Internally Illuminated Flashing Arrow”.

SECTION 6. USE OF TRAFFIC DRUMS AND TRAFFIC CONES

6.a) Traffic drums shall be used for taper channelization on limited-access roadways, ramps, and turning roadways and to delineate raised catch basins and other hazards.

6.b) Traffic drums shall be used in place of traffic cones in traffic control patterns that are in effect for more than a 36-hour duration.

6.c) Traffic Cones less than 42 inches in height shall not be used on limited-access roadways or on non-limited access roadways with a posted speed limit of 45 mph and above.

6.d) Typical spacing of traffic drums and/or cones shown on the Traffic Control Plans in the Contract are maximum spacings and may be reduced to meet actual field conditions as required.

SECTION 7. USE OF (REMOTE CONTROLLED) CHANGEABLE MESSAGE SIGNS (CMS)

7.a) For lane closures on limited access roadways, one CMS shall be used in advance of the traffic control pattern. Prior to installing the pattern, the CMS shall be installed and in operation, displaying the appropriate lane closure information (i.e.: Left Lane Closed - Merge Right). The CMS shall be positioned $\frac{1}{2}$ - 1 mile ahead of the lane closure taper. If the nearest Exit ramp is greater than the specified $\frac{1}{2}$ - 1 mile distance, than an additional CMS shall be positioned a sufficient distance ahead of the Exit ramp to alert motorists to the work and therefore offer them an opportunity to take the exit.

7.b) CMS should not be installed within 1000 feet of an existing CMS.

7.c) On non-limited access roadways, the use of CMS for lane closures is optional. The roadway geometry, sight line distance, and traffic volume should be considered in the decision to use the CMS.

7.d) The advance CMS is typically placed off the right shoulder, 5 feet from the edge of pavement. In areas where the CMS cannot be placed beyond the edge of pavement, it may be placed on the paved shoulder with a minimum of five (5) traffic drums placed in a taper in front of it to delineate its position. The advance CMS shall be adequately protected if it is used for a continuous duration of 36 hours or more.

7.e) When the CMS are no longer required, they should be removed from the clear zone and have the display screen cleared and turned 90° away from the roadway.

7.f) The CMS generally should not be used for generic messages (ex: Road Work Ahead, Bump Ahead, Gravel Road, etc.).

7.g) The CMS should be used for specific situations that need to command the motorist's attention which cannot be conveyed with standard construction signs (Examples include: Exit 34 Closed Sat/Sun - Use Exit 35, All Lanes Closed - Use Shoulder, Workers on Road - Slow Down).

7.h) Messages that need to be displayed for long periods of time, such as during stage construction, should be displayed with construction signs. For special signs, please coordinate with the Office of Construction and the Division of Traffic Engineering for the proper layout/dimensions required.

7.i) The messages that are allowed on the CMS are as follows:


<u>Message No.</u>	<u>Frame 1</u>	<u>Frame 2</u>	<u>Message No.</u>	<u>Frame 1</u>	<u>Frame 2</u>
1	LEFT LANE CLOSED	MERGE RIGHT	9	LANES CLOSED AHEAD	REDUCE SPEED
2	2 LEFT LANES CLOSED	MERGE RIGHT	10	LANES CLOSED AHEAD	USE CAUTION
3	LEFT LANE CLOSED	REDUCE SPEED	11	WORKER S ON ROAD	REDUCE SPEED
4	2 LEFT LANES CLOSED	REDUCE SPEED	12	WORKER S ON ROAD	SLOW DOWN
5	RIGHT LANE CLOSED	MERGE LEFT	13	EXIT XX CLOSED	USE EXIT YY
6	2 RIGHT LANES CLOSED	MERGE LEFT	14	EXIT XX CLOSED USE YY	FOLLOW DETOUR
7	RIGHT LANE CLOSED	REDUCE SPEED	15	2 LANES SHIFT AHEAD	USE CAUTION
8	2 RIGHT LANES CLOSED	REDUCE SPEED	16	3 LANES SHIFT AHEAD	USE CAUTION

For any other message(s), approval must be received from the Office of Construction prior to their use. No more than two (2) displays shall be used within any message cycle.


SECTION 8. USE OF STATE POLICE OFFICERS

- 8.a) State Police may be utilized only on limited access highways and secondary roadways under their primary jurisdiction. One Officer may be used per critical sign pattern. Shoulder closures and right lane closures can generally be implemented without the presence of a State Police Officer. Likewise in areas with moderate traffic and wide, unobstructed medians, left lane closures can be implemented without State Police presence. Under some situations it may be desirable to have State Police presence, when one is available. Examples of this include: nighttime lane closures; left lane closures with minimal width for setting up advance signs and staging; lane and shoulder closures on turning roadways/ramps or mainline where sight distance is minimal; and closures where extensive turning movements or traffic congestion regularly occur, however they are not required.
- 8.b) Once the pattern is in place, the State Police Officer should be positioned in a non-hazardous location in advance of the pattern. If traffic backs up beyond the beginning of the pattern, then the State Police Officer shall be repositioned prior to the backup to give warning to the oncoming motorists. The State Police Officer and TMA should not be in proximity to each other.
- 8.c) Other functions of the State Police Officer(s) may include:
 - Assisting entering/exiting construction vehicles within the work area.
 - Enforcement of speed and other motor vehicle laws within the work area, if specifically requested by the project.
- 8.d) State Police Officers assigned to a work site are to only take direction from the Engineer.

SERIES 16 SIGNS



16-E	80-1605	W 84" x 60"	H
16-H	80-1608	60" x 42"	
16-M	80-1613	30" x 24"	



16-S	80-1619	W 48" x 30"	H
------	---------	----------------	---

THE 16-S SIGN SHALL BE USED ON ALL PROJECTS THAT REQUIRE SIDEWALK RECONSTRUCTION OR RESTRICT PEDESTRIAN TRAVEL ON AN EXISTING SIDEWALK.

SERIES 16 SIGNS SHALL BE INSTALLED IN ADVANCE OF THE TRAFFIC CONTROL PATTERNS TO ALLOW MOTORISTS THE OPPORTUNITY TO AVOID A WORK ZONE. SERIES 16 SIGNS SHALL BE INSTALLED ON ANY MAJOR INTERSECTING ROADWAYS THAT APPROACH THE WORK ZONE. ON LIMITED-ACCESS HIGHWAYS, THESE SIGNS SHALL BE LOCATED IN ADVANCE OF THE NEAREST UPSTREAM EXIT RAMP AND ON ANY ENTRANCE RAMPS PRIOR TO OR WITHIN THE WORK ZONE LIMITS.

THE LOCATION OF SERIES 16 SIGNS CAN BE FOUND ELSEWHERE IN THE PLANS OR INSTALLED AS DIRECTED BY THE ENGINEER.

SIGNS 16-E AND 16-H SHALL BE POST-MOUNTED.

SIGN 16-E SHALL BE USED ON ALL EXPRESSWAYS.

SIGN 16-H SHALL BE USED ON ALL RAMPS, OTHER STATE ROADWAYS, AND MAJOR TOWN/CITY ROADWAYS.

SIGN 16-M SHALL BE USED ON OTHER TOWN ROADWAYS.


REGULATORY SIGN "ROAD WORK AHEAD, FINES DOUBLED"

THE REGULATORY SIGN "ROAD WORK AHEAD FINES DOUBLED" SHALL BE INSTALLED FOR ALL WORK ZONES THAT OCCUR ON ANY STATE HIGHWAY IN CONNECTICUT WHERE THERE ARE WORKERS ON THE HIGHWAY OR WHEN THERE IS OTHER THAN EXISTING TRAFFIC OPERATIONS.

THE "ROAD WORK AHEAD FINES DOUBLED" REGULATORY SIGN SHALL BE PLACED AFTER THE SERIES 16 SIGN AND IN ADVANCE OF THE "ROAD WORK AHEAD" SIGN.

"END ROAD WORK" SIGN

THE LAST SIGN IN THE PATTERN MUST BE THE "END ROAD WORK" SIGN.



SCALE: NONE



CONSTRUCTION TRAFFIC CONTROL PLAN
REQUIRED SIGNS

NOTES FOR TRAFFIC CONTROL PLANS

1. IF A TRAFFIC STOPPAGE OCCURS IN ADVANCE OF SIGN (A), THEN AN ADDITIONAL SIGN (A) SHALL BE INSTALLED IN ADVANCE OF THE STOPPAGE.
2. SIGNS (A), (B), AND (D) SHOULD BE OMITTED WHEN THESE SIGNS HAVE ALREADY BEEN INSTALLED TO DESIGNATE A LARGER WORK ZONE THAN THE WORK ZONE THAT IS ENCOMPASSED ON THIS PLAN.
3. SEE TABLE 1 FOR ADJUSTMENT OF TAPERS IF NECESSARY.
4. IF THIS PLAN REMAINS IN CONTINUOUS OPERATION FOR MORE THAN 36 HOURS, THEN TRAFFIC DRUMS SHALL BE USED IN PLACE OF TRAFFIC CONES.
5. ANY LEGAL SPEED LIMIT SIGNS WITHIN THE LIMITS OF A ROADWAY / LANE CLOSURE AREA SHALL BE COVERED WITH AN OPAQUE MATERIAL WHILE THE CLOSURE IS IN EFFECT, AND UNCOVERED WHEN THE ROADWAY / LANE CLOSURE IS RE-OPENED TO ALL LANES OF TRAFFIC.
6. IF THIS PLAN REMAINS IN CONTINUOUS OPERATION FOR MORE THAN 36 HOURS, THEN ANY EXISTING CONFLICTING PAVEMENT MARKINGS SHALL BE ERADICATED OR COVERED, AND TEMPORARY PAVEMENT MARKINGS THAT DELINEATE THE PROPER TRAVELPATHS SHALL BE INSTALLED.
7. DISTANCES BETWEEN SIGNS IN THE ADVANCE WARNING AREA MAY BE REDUCED TO 100' ON LOW-SPEED URBAN ROADS (SPEED LIMIT < 40 MPH).
8. IF THIS PLAN IS TO REMAIN IN OPERATION DURING THE HOURS OF DARKNESS, INSTALL BARRICADE WARNING LIGHTS - HIGH INTENSITY ON ALL POST-MOUNTED DIAMOND SIGNS IN THE ADVANCE WARNING AREA.
9. A CHANGEABLE MESSAGE SIGN SHALL BE INSTALLED ONE HALF TO ONE MILE IN ADVANCE OF THE LANE CLOSURE TAPER.
10. SIGN (P) SHALL BE MOUNTED A MINIMUM OF 7 FEET FROM THE PAVEMENT SURFACE TO THE BOTTOM OF THE SIGN.

TABLE 1 - MINIMUM TAPER LENGTHS

POSTED SPEED LIMIT (MILES PER HOUR)	MINIMUM TAPER LENGTH FOR A SINGLE LANE CLOSURE
30 OR LESS	180' (55m)
35	250' (75m)
40	320' (100m)
45	540' (165m)
50	600' (180m)
55	660' (200m)
65	780' (240m)

METRIC CONVERSION CHART (1" = 25mm)

ENGLISH	METRIC	ENGLISH	METRIC	ENGLISH	METRIC
12"	300mm	42"	1050mm	72"	1800mm
18"	450mm	48"	1200mm	78"	1950mm
24"	600mm	54"	1350mm	84"	2100mm
30"	750mm	60"	1500mm	90"	2250mm
36"	900mm	66"	1650mm	96"	2400mm




SCALE: NONE

CONSTRUCTION TRAFFIC CONTROL PLAN

NOTES

WORK IN RIGHT LANE - 4 LANE UNDIVIDED HIGHWAY

SIGN FACE
86 SQ. FT (MIN.)



TRAFFIC CONE **OR** TRAFFIC DRUM

* OPTIONAL TRAFFIC DRUM PORTABLE SIGN SUPPORT

← HIGH MOUNTED INTERNALLY ILLUMINATED FLASHING ARROW

CONSTRUCTION TRAFFIC CONTROL PLAN


PLAN 10


SEE NOTES 1, 2, 3, 4, 5, 6, 7, 8


CONNECTICUT DEPARTMENT OF TRANSPORTATION
BUREAU OF ENGINEERING & CONSTRUCTION

APPROVED

Charles S. Harlow
2012.06.05 15:54:15-04'00'
PRINCIPAL ENGINEER







WORK IN TRAVEL LANE AND SHOULDER
TWO LANE HIGHWAY
ALTERNATING ONE-WAY TRAFFIC OPERATIONS

SIGN FACE
108 SQ. FT (MIN.)

HAND SIGNAL METHODS TO BE USED BY UNIFORMED FLAGGERS

THE FOLLOWING METHODS FROM SECTION 6E.07, FLAGGER PROCEDURES, IN THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES," SHALL BE USED BY UNIFORMED FLAGGERS WHEN DIRECTING TRAFFIC THROUGH A WORK AREA. THE STOP/SLOW SIGN PADDLE (SIGN NO. 80-9950) SHOWN ON THE TRAFFIC STANDARD SHEET TR-1220 01 ENTITLED, "SIGNS FOR CONSTRUCTION AND PERMIT OPERATIONS" SHALL BE USED.

A. TO STOP TRAFFIC

TO STOP ROAD USERS, THE FLAGGER SHALL FACE ROAD USERS AND AIM THE STOP PADDLE FACE TOWARD ROAD USERS IN A STATIONARY POSITION WITH THE ARM EXTENDED HORIZONTALLY AWAY FROM THE BODY. THE FREE ARM SHALL BE HELD WITH THE PALM OF THE HAND ABOVE SHOULDER LEVEL TOWARD APPROACHING TRAFFIC.



B. TO DIRECT TRAFFIC TO PROCEED

TO DIRECT STOPPED ROAD USERS TO PROCEED, THE FLAGGER SHALL FACE ROAD USERS WITH THE SLOW PADDLE FACE AIMED TOWARD ROAD USERS IN A STATIONARY POSITION WITH THE ARM EXTENDED HORIZONTALLY AWAY FROM THE BODY. THE FLAGGER SHALL MOTION WITH THE FREE HAND FOR ROAD USERS TO PROCEED.



C. TO ALERT OR SLOW TRAFFIC

TO ALERT OR SLOW TRAFFIC, THE FLAGGER SHALL FACE ROAD USERS WITH THE SLOW PADDLE FACE AIMED TOWARD ROAD USERS IN A STATIONARY POSITION WITH THE ARM EXTENDED HORIZONTALLY AWAY FROM THE BODY. TO FURTHER ALERT OR SLOW TRAFFIC, THE FLAGGER HOLDING THE SLOW PADDLE FACE TOWARD ROAD USERS MAY MOTION UP AND DOWN WITH THE FREE HAND, PALM DOWN.



TRAFFIC CONE TRAFFIC DRUM
* OPTIONAL TRAFFIC DRUM PORTABLE SIGN SUPPORT
 HIGH MOUNTED INTERNALLY ILLUMINATED FLASHING ARROW




SCALE: NONE

CONSTRUCTION TRAFFIC CONTROL PLAN
PLAN 13 - SHEET 2 OF 2
SEE NOTES 1, 2, 4, 6, 7, 8


APPROVED

Charles S. Harlow
Charles S. Harlow
2012.06.05 15:55:45-04'00'
PRINCIPAL ENGINEER



WORK IN TRAVEL LANE AND SHOULDER
TWO LANE HIGHWAY

SIGN FACE
62 SQ. FT (MIN.)



D 80-9612

END
ROAD WORK

2'

AA 31-1906

4'

3.5'

ROAD WORK
AHEAD
FINES
DOUBLED

- TRAFFIC CONE **OR** TRAFFIC DRUM
- OPTIONAL TRAFFIC DRUM PORTABLE SIGN SUPPORT
- HIGH MOUNTED INTERNALLY ILLUMINATED FLASHING ARROW



SCALE: NONE

CONSTRUCTION TRAFFIC CONTROL PLAN


PLAN 15

SEE NOTES 1, 2, 4, 6, 7, 8

CONNECTICUT DEPARTMENT OF TRANSPORTATION
BUREAU OF ENGINEERING & CONSTRUCTION


APPROVED

Charles S. Harlow
2012.06.05 15:56:29-04'00'
PRINCIPAL ENGINEER



WORK IN MIDDLE OF ROADWAY AT INTERSECTION

SIGN FACE
144 SQ. FT (MIN.)



TRAFFIC CONE **OB** TRAFFIC DRUM

* OPTIONAL TRAFFIC DRUM PORTABLE SIGN SUPPORT

← HIGH MOUNTED INTERNALLY ILLUMINATED FLASHING ARROW



SCALE: NONE

CONSTRUCTION TRAFFIC CONTROL PLAN


PLAN 17

SEE NOTES 1, 2, 4, 6, 7, 8

CONNECTICUT DEPARTMENT OF TRANSPORTATION
BUREAU OF ENGINEERING & CONSTRUCTION

APPROVED

Charles S. Harlow
2012.06.05 15:57:16-04'00'



Article 9.71.05 – Basis of Payment is supplemented by the following:

The temporary relocation of signs and supports, and the furnishing, installation and removal of any temporary supports shall be paid for under the item “Maintenance and Protection of Traffic”. Temporary overhead sign supports and foundations shall be paid for under the appropriate item(s).

The cost of furnishing, installing, and removing the material for the 4H:1V traversable slope shall be paid for under the item “Maintenance and Protection of Traffic.”

ITEM# 1017032A - SERVICE (METERED)

Description:

Furnish and install a metered electric service at the location shown on the plans or as directed by the Engineer.

Materials:

- Meter Socket
 - UL listed
 - Manual lever bypass
 - P.V.C Slip fitting that complies with Utility Company requirements.
 - Locking metal cover for the glass enclosure
 - Contact the serving utility company for a list of approved meter sockets
- Conduit Bond Clamp
 - UL listed
 - Rated for direct burial

Locations served by United Illuminating (UI) or Wallingford Electric Division (WED)

Meter socket rated at 100 amps

Locations served by Eversource (formerly Connecticut Light and Power Co. [CL&P])

Meter socket rated at 200 amps

Enclosure capable of accepting a 3 inch (75 mm) rigid metal conduit (RMC)

Construction Methods:

Comply with the National Electric Code (NEC), Public Utility Regulatory Authority (PURPA), and the serving power company requirements. Install a meter socket with associated equipment on the outside of the controller cabinet, as shown on the plans. Mount the enclosure approximately 54 inches (1.37 meters) above the ground. Install an expansion fitting in the RMC between the ground and the enclosure. Attach a direct-buried bond clamp to the service RMC below ground level, adjacent to the foundation. Bond the service conduit to the controller cabinet ground rod. Install a continuous nylon pull rope of at least 200 lbs (90 Kg) breaking strength in the conduit between the meter socket and the service source. Ensure all circuit breakers are off when service is connected by the utility company. The work must be inspected and approved by the Engineer or his designated representative prior to scheduling a service connection. Record the meter number and the date service is connected for billing purposes.

Service Request

- Traffic Signal on State Road: Contact the CT DOT Traffic Electrical office to complete the necessary service request forms.
- Traffic Signal on Town Road: Complete all necessary request forms and forward to the appropriate power company office.
- Incident Management Site: Complete all necessary request forms and forward to the appropriate power company office.

Locations served by United Illuminating

Contact the UI office to have a Job Number assigned. When the work is complete notify the Engineer to inspect and confirm that the work is according to the National Electric Code. Request that the Engineer contact the United Illuminating, Work in Progress office, to report the job number and to schedule a service connection.

Locations served by Wallingford Electric Division

Contact the Electric Division, Engineering Office to arrange for service and/or to schedule work by the Electric Division on utility poles above 10 feet (3 meters). When the work is complete notify the Engineer to inspect and confirm that the work is according to the National Electric Code. Request that the Engineer contact the Electric Division 24 hours prior to the desired connection date.

Locations served by Eversource and all other electric power providers

Contact the power company engineering representative for exact requirements of the service. All riser fees and any other installation charges required of an underground metered service are the responsibility of the Contractor. When the work is complete notify the Engineer to inspect and confirm that the work is according to the National Electric Code. Request that the Engineer contact the power company to schedule the connection.

Method of Measurement:

The installation of the Service (Metered) will be measured for payment by the number of metered electric services of the type specified, completed, with service connected, and accepted in place.

Basis of Payment:

This work will be paid for at the contract unit price each for "Service (Metered)" complete and accepted in place. The price shall include all material above ground such as the meter socket enclosure, surface conduit, expansion fitting, coupling, and load side service conductors. The price shall also include the direct-buried ground clamp, bonding wire, pull rope, all material, equipment, tools, labor and incidentals necessary.

The power company will provide the line-side conductors and the meter.

ITEM #1105503A - FLASHER CABINET

DESCRIPTION:

This item shall consist of furnishing and installing a Flasher Cabinet and Flasher at the location shown on the plans and in conformity with specifications.

MATERIALS:

Each cabinet shall be made of rigid metal with a suitable finish. The cabinet shall be of clean-cut design and appearance and shall be substantially constructed of aluminum. The pedestal-mounted and pole-mounted cabinets shall be approximately 12 3/4" (325mm) x 16" (406mm) x 25" (635mm) in size or the equivalent in volume. The cabinet shall have a main door which shall be equipped with a special CONN-1 lock and key. Door hinge pins shall be of stainless steel material. Two keys shall be furnished for each lock. When closed, doors shall fit tightly to neoprene gasket material. The cabinet shall contain a suitably designed vent for the purpose of releasing any explosive gases which may enter the cabinet.

All panel wiring shall be neat and firm, and the panel which shall be mounted in the rear of the cabinet shall mount the following:

1. Neutral Bus Bar, for neutral side of power supply line. This Bus Bar shall be rated for 30 amperes.
2. Terminals for conductors of cable - one for each circuit and one or more terminals for the common conductors. This terminal bus shall be rated for 30 amperes. No pressure-type terminal blocks will be accepted.
3. A one piece 120 volt convenience outlet and lamp receptacle. A heavy duty 15 ampere circuit breaker shall be mounted on the left side of the cabinet.

The cabinet shall have a hole for cable entrance into the bottom of the cabinet of at least 2" (50mm) in diameter. There shall be an adapter for mounting the cabinet on a 4" (100mm) pipe.

All conductors shall be provided with lugs for attachment to binding posts. Combining of conductors to one lug will not be allowed. Non-hygrosopic materials, having good insulating qualities, shall be used for all insulating purposes. All internal wiring shall be #14 AWG stranded copper. Wiring shall be cabled.

FLASHER:

Two (2) Circuit Solid State: The Flasher shall conform to the latest NEMA Publication, Part 8, with the following additions:

Only type 2 Flashers will be accepted. The output shall be from optically-isolated solid state relays. The Flasher shall have L.E.D. indicators connected to the output for visual reference.

The radio interference filter shall be designed to operate on 15 amperes, 120 volts, 60 cycle A.C. and shall meet the standards of the Underwriters Laboratory and the Radio and Television Manufacturer's Association.

All flashers inputs and outputs shall be wired to a terminal block in the cabinet.

Flasher jack panel to be of the female type.

CONSTRUCTION METHODS:

The cabinet shall be mounted at the location shown on the plans or as directed by the Engineer.

METHOD OF MEASUREMENT:

This item shall be measured for payment by the actual number of "Flasher Cabinets" installed and accepted.

BASIS OF PAYMENT:

This item shall be paid for at the contract unit price each for "Flasher Cabinet" which price shall include mounting hardware, tools, labor and incidentals.

ITEM #1107007A - PEDESTRIAN PUSHBUTTON AND SIGN (PIEZO)

Article 11.07.05: Basis of Payment:

Insert the following after the word saddle: "Extension Brackets,"

Article M16.08 - Pedestrian Push Button:

Delete the entire section and replace with the following:

A. General

- Size and force compliant with ADA, Section 14.2.5, Crossing Controls.
- Tamper-proof, and Vandal-proof, Weatherproof, Freeze-proof, Impact-resistant design and construction.
- Completely insulated to preclude electrical shock under any weather conditions.
- Wire entrance through the rear.
- Stainless steel mounting hardware.

B. Actuation

1. Mechanical:

- Single momentary contact switch with tactile feedback.
- Rated at 10 amps, 125 volts.
- Normally open, closed when actuated.

2. Piezo:

- Either non-movable or minimal movement (< 1/16" (1.6)) pressure activation.
- Audible confirmation beep to correspond with circuit closure.
- Minimum 100,000,000 actuations.

C. Housing

- Die cast aluminum meeting requirements of ASTM B85.
- Designed to attach 9" x 12" (230 x 300) four-hole advisory sign.
- Flat back to facilitate surface mount.
- Available hardware to either pedestal top-mount or pole side-mount on diameter range of 3½" (89) to 15" (380).
- Available extension bracket of a size indicated on the plan – 18" maximum.

D. Finish

• Method: Either

1. Painted with 3 coats of infrared oven-baked paint before assembly.
 - Primer: Baked iron oxide which meets or exceeds FS TT-P-636.
 - Second coat: Exterior-baking enamel, light gray, which meets or exceeds FS TT-E-527.
 - Third coat: Exterior-baking enamel, which meets or exceeds FS TT-E-489.
2. Electrostatic powder coated after chemically cleaned.

• Color:

The housing and all brackets and hardware shall be black by the manufacturer. The color shall be No. 17038, Federal Standard No. 595.

At intersections at Merritt Parkway interchanges, the housing and all brackets and hardware shall be dark green by the manufacturer. The color shall be No. 14056, Federal Standard No. 595.

ITEM # 1108163A - MODIFY EXISTING CONTROLLER

This item shall consist of modifying the existing traffic controller assembly to provide the revised operation as shown on the plans or as directed by the Engineer. The modification shall include, but not be limited to, revisions to the timing and sequence, cabinet wiring, coordination, pre-emption, field wiring and cabinet wiring diagrams.

MATERIAL

The material for this work shall conform to the requirements of the current edition of the Connecticut Department of Transportation Functional Specifications for Traffic Control Equipment. The material shall be compatible with the existing equipment. Any material in question shall be approved prior to installation by the Engineer or the Department of Transportation Signal Lab, 280 West Street, Rocky Hill. Contact Mr. Don Assard at (860) 258-0346 or Mr. Mark Zampini at (860) 258-0349 for approval.

CONSTRUCTION METHODS

All revisions to the cabinet wiring shall be neat and orderly. All additional wiring shall be from terminal to terminal. Splices will not be allowed. All changes, additions and deletions shall be documented, dated and drawn on the reproducible original or a reproducible copy of the original cabinet wiring diagram. Four paper copies shall be furnished to the Engineer upon completion of the revision.

METHOD OF MEASUREMENT

This item will be measured for payment as an "Each" item.

BASIS OF PAYMENT

This item will be paid for at the contract price each, for "Modify Existing Controller" which price shall include all necessary load switches, relays, components, hardware, tools, equipment, engineering and labor required to modify the existing controller as shown on the plan. This price shall also include four updated cabinet wiring diagrams.

<i>Pay Item</i>	<i>Pay Unit</i>
Modify Existing Controller	Ea.

ITEM # 1117111A –RECTANGULAR RAPID FLASHING BEACON (RRFB) TYPE B

Description:

Furnish and install a pedestrian actuated rectangular rapid flashing beacon (RRFB) at the location indicated on the plan or where directed by the Engineer.

General Requirements:

Each RRFB will be a complete assembly, consisting of indications, controller cabinet (circuit breaker, timer or solid-state circuit boards etc.) or any electrical component hardware.

Type B: Two sided RRFB will contain six rectangular indications, two on each side facing traffic, and one indication on each end, visible to pedestrians in the cross walk.

Functional Requirement:

When actuated, the two yellow indications in each RRFB unit shall flash in a rapidly flashing sequence.

Each of the two yellow indications of an RRFB shall provide 75 flashing sequences per minute. During each 800-millisecond flashing sequence, the left and right RRFB indications shall operate using the following sequence:

The RRFB indication on the left-hand side shall be illuminated for approximately 50 milliseconds.

Both RRFB indications shall be dark for approximately 50 milliseconds.

The RRFB indication on the right-hand side shall be illuminated for approximately 50 milliseconds.

Both RRFB indications shall be dark for approximately 50 milliseconds.

The RRFB indication on the left-hand side shall be illuminated for approximately 50 milliseconds.

Both RRFB indications shall be dark for approximately 50 milliseconds.

The RRFB indication on the right-hand side shall be illuminated for approximately 50 milliseconds.

Both RRFB indications shall be dark for approximately 50 milliseconds.

Both RRFB indications shall be illuminated for approximately 50 milliseconds.

Both RRFB indications shall be dark for approximately 250 milliseconds.

The flash rate of each individual RRFB indication, as applied over the full flashing sequence, shall not be between 5 and 30 flashed per second to avoid frequencies that might cause seizures.

The light intensity of the yellow indications during daytime conditions shall meet the minimum specifications for Class 1 Yellow Peak Luminous Intensity in the Society of Automotive Engineers (SAE) Standard J595 (Directional Flashing Optical Warning Devices for Authorized Emergency, Maintenance, and Service Vehicles) dated January 2005.

Each RRFB indication will be activated by an ADA compliant (piezo) pedestrian pushbutton and operation will cease after a predetermined time limit (based on MUTCD procedures).

All RRFBs associated with a given crosswalk (including those with an advance crossing sign, if used) shall, when activated, simultaneously commence operation of their alternating rapid flashing indications and shall cease operation simultaneously.

Mechanical and Electrical Requirements:

a) Dimensions:

Type B: - Two sided/6 LEDs.....3.25”H x 20”W x 8”D

b) Power: - 120VAC

c) Temperature: - All components will be capable of continuous operation over a temperature range of -30 DEG. F to 165 DEG. F

d) Indications: - Daylight distance visibility....> 1000 feet
- Night distance visibility.....> 1 mile
- Flash Pattern.....Wig-Wag
- Optics.....Polycarbonate Lenses
- Color.....Yellow
- Body.....Powder Coated Federal Yellow
- Size.....5" wide x 2" high

e) Housing: - Powder Coated Federal Yellow

Construction Method:

Each RRFB indication will be mounted horizontally to a standard 4 1/2" diameter aluminum pedestal and in accordance with dimensions and details shown on the plan.

The two RRFB indications shall be aligned horizontally, with the longer dimension horizontal and with a minimum space between the two indications of approximately seven inches (7 in), measured from inside edge of one indication to inside edge of the other indication.

The outside edges of the RRFB indications, including any housings, shall not project beyond the outside edges of the sign.

Method of Measurements:

This work will be measured as the number of RRFBs furnished, installed and accepted in place.

Basis of Payment:

This work will be paid for at the contract unit price of each "Rectangular Rapid Flashing Beacon (RRFB)" of the type specified which will include the cost of conduit fittings, hardware, controller cabinet complete with all necessary equipment, ground rod, armored ground cable, wiring, paint and all materials, equipment, tools and labor included thereto.

Pay Item
Rectangular Rapid Flashing Beacon (RRFB) Type B

Pay Unit
ea. (ea.)

ITEM#1118012A REMOVAL AND/OR RELOCATION OF TRAFFIC SIGNAL EQUIPMENT

Section 11.18: Replace the entire section with the following:

11.18.01 – Description:

Remove all abandon traffic signal equipment. Restore the affected area. Where indicated on the plans remove and reinstall existing traffic signal equipment to the location(s) shown.

11.18.02 – Materials:

The related sections of the following specifications apply to all incidental and additional material required for the proper relocation of existing equipment and the restoration of any area affected by this work.

- Division III, “Materials Section” of the Standard Specifications.
- Current Supplemental Specifications to the Standard Specifications.
- Applicable Special Provisions to the Standard Specifications.
- Current Department of Transportation, Functional Specifications for Traffic Control Equipment.

Article 11.18.03 - Construction Methods:

Schedule/coordinate the removal and/or relocation of existing traffic signal equipment with the installation of new equipment to maintain uninterrupted traffic signal control. This includes but is not limited to vehicle signals and detectors, pedestrian signals and pushbuttons, co-ordination, and pre-emption.

Abandoned Equipment

The contract traffic signal plan usually does not show existing equipment that will be abandoned. Consult the existing traffic signal plan for the location of abandoned material especially messenger strand, conduit risers, and handholes that are a distance from the intersection. A copy of the existing plan is usually in the existing controller cabinet. If not, a plan is available from the Division of Traffic Engineering upon request.

Unless shown on the plans it is not necessary to remove abandoned conduit in-trench and conduit under-roadway

When a traffic signal support strand, rigid metal conduit, down guy, or other traffic signal equipment is attached to a utility pole, secure from the pole custodian permission to work on the pole. All applicable Public Utility Regulatory Authority (PURPA) regulations and utility company requirements govern. Keep utility company apprised of the schedule and the nature of the work.

Remove all abandoned hardware, conduit risers, and down guys, Remove anchor rods, to 6" (150mm) below grade.

When underground material is removed, backfill the excavation with clean fill material. Compact the fill to eliminate settling. Remove entirely the following material: pedestal foundation; controller foundation; handhole; pressure sensitive vehicle detector complete with concrete base. Unless otherwise shown on the plan, remove steel pole and mast arm foundation to a depth of 2 feet (600mm) below grade. Restore the excavated area to a grade and condition compatible with the surrounding area.

- If in an unpaved area apply topsoil and establish turf in accordance with Section 9.44 and Section 9.50 of the Standard Specifications.
- If in pavement or sidewalk, restore the excavated area in compliance with the applicable Sections of Division II, "Construction Details" of the Standard Specifications.

Relocated Equipment

In the presence of the Engineer, verify the condition of all material that will be relocated and reused at the site. Carefully remove all material, fittings, and attachments in a manner to safeguard parts from damage or loss. Replace at no additional cost, all material which becomes damaged or lost during removal, storage, or reinstallation.

Salvage Equipment

Salvage Material	Stock No.	Value
Aluminum Pedestal 8 foot (2.4 m)	330-16-7108	\$ 100.00

All material not listed as salvage becomes the property of the Contractor. Properly handle, transport, then dispose in a suitable dump or recycle this material. Comply with all Federal and State hazardous waste laws and regulations.

In the presence of the Engineer, verify the condition and quantity of salvage material prior to removal. After removal transport and store the material protected from moisture, dirt, and other damage. Coil and secure copper cable separate from other cable such as galvanized support strand.

Within 4 working days of removal, return the Town owned salvage material to the Town Highway Department listed below. Supply all necessary manpower and equipment to load, transport, and unload the material. The condition and quantity of the material after unloading will be verified by the Engineer.

366 Church Hill Road
Trumbull, CT

Municipal Owned Traffic Signal Equipment

Return all municipal owned material such as pre-emption equipment to the Town.

Article 11.18.04 – Method of Measurement:

This work will be measured as a Lump Sum.

Article 11.18.05 – Basis of Payment:

This work will be paid for at the contract lump sum price for “Removal and/or Relocation of Traffic Signal Equipment” which price shall include relocating signal equipment and associated hardware, all equipment, material, tools and labor incidental thereto. This price shall also include removing, loading, transporting, and unloading of signal equipment/materials designated for salvage and all equipment, material, tools and labor incidental thereto. This price shall also include removing and disposing of traffic signal equipment not to be salvaged and all equipment, material, tools and labor incidental thereto.

Payment is at the contract lump sum price for “Removal and/or Relocation of Traffic Signal Equipment” inclusive of all labor, vehicle usage, storage, and incidental material necessary for the complete removal of abandoned equipment/material and/or relocation of existing traffic signal equipment/material. Payment will also include the necessary labor, equipment, and material for the complete restoration of all affected areas.

A credit will be calculated and deducted from monies due the Contractor equal to the listed value of salvage material not returned or that has been damaged and deemed unsalvageable due to the Contractor’s operations.

Pay Item	Pay Unit
Removal and/or Relocation of Traffic Signal Equipment	L.S. (L.S.)

ITEM NO. 1206023A - REMOVAL AND RELOCATION OF EXISTING SIGNS

Section 12.06 is supplemented as follows:

Article 12.06.01 – Description is supplemented with the following:

Work under this item shall consist of the removal and/or relocation of designated side-mounted extruded aluminum and sheet aluminum signs, sign posts, sign supports, and foundations where indicated on the plans or as directed by the Engineer. Work under this item shall also include furnishing and installing new sign posts and associated hardware for signs designated for relocation.

Article 12.06.03 – Construction Methods is supplemented with the following:

The Contractor shall take care during the removal and relocation of existing signs, sign posts, and sign supports that are to be relocated so that they are not damaged. Any material that is damaged shall be replaced by the Contractor at no cost to the State.

Foundations and other materials designated for removal shall be removed and disposed of by the Contractor as directed by the Engineer and in accordance with existing standards for Removal of Existing Signing.

Sheet aluminum signs designated for relocation are to be re-installed on new sign posts.

Article 12.06.04 – Method of Measurement is supplemented with the following:

Payment under Removal and Relocation of Existing Signs shall be at the contract lump sum price which shall include all extruded aluminum and sheet aluminum signs, sign posts, and sign supports designated for relocation, all new sign posts and associated hardware for signs designated for relocation, all extruded aluminum signs, sheet aluminum signs, sign posts and sign supports designated for scrap, and foundations and other materials designated for removal and disposal, and all work and equipment required.

Article 12.06.05 – Basis of Payment is supplemented with the following:

This work will be paid for at the contract lump sum price for “Removal and Relocation of Existing Signs” which price shall include relocating designated extruded aluminum and sheet aluminum signs, sign posts, and sign supports, providing new posts and associated hardware for relocated signs, removing and disposing of foundations and other materials, and all equipment, material, tools and labor incidental thereto. This price shall also include removing, loading, transporting, and unloading of extruded aluminum signs, sheet aluminum signs, sign posts, and sign supports designated for scrap and all equipment, material, tools and labor incidental thereto.

Pay Item

Removal and Relocation of Existing Signs

Pay Unit

L.S.

ITEM #1208931A—SIGN FACE - SHEET ALUMINUM (TYPE IX RETROREFLECTIVE SHEETING)

ITEM #1208932A—SIGN FACE - SHEET ALUMINUM (TYPE IV RETROREFLECTIVE SHEETING)

Section 12.08 is supplemented and amended as follows:

12.08.01—Description:

Add the following:

This item shall also include field testing of metal sign base posts as directed by the Engineer.

12.08.03—Construction Methods:

Delete the last sentence and add the following:

Metal sign base posts shall be whole and uncut. Sign base post embedment and reveal lengths shall be as shown on the plans. The Contractor shall drive the metal sign base posts by hand tools, by mechanical means or by auguring holes. If an obstruction is encountered while driving or placing the metal sign base post, the Contractor shall notify the Engineer who will determine whether the obstruction shall be removed, the sign base post or posts relocated, or the base post installation in ledge detail shall apply. Backfill shall be thoroughly tamped after the posts have been set level and plumb.

Field Testing of Metal Sign Posts: When the sign installations are complete, the Contractor shall notify the Engineer the Project is ready for field testing. Based on the number of posts in the Project, the Engineer will select random sign base posts which shall be removed by the Contractor for inspection and measurement by the Engineer. After such inspection is completed at each base post location, the Contractor shall restore or replace such portions of the work to the condition required by the Contract. Refer to the table in 12.08.05 for the number of posts to be field tested.

12.08.04—Method of Measurement:

Add the following:

The work required to expose and measure sign base post length and embedment depth using field testing methods, and restoration of such work, will not be measured for payment and shall be included in the general cost of the work.

12.08.05—Basis of Payment:

Replace the entire Article with the following:

This work will be paid for at the Contract unit price per square foot for “Sign Face - Sheet Aluminum” of the type specified complete in place, adjusted by multiplying by the applicable Pay Factor listed in the table below. The price for this work shall include the completed sign, metal sign post(s), span-mounted sign brackets and mast arm-mounted brackets, mounting hardware, including reinforcing plates, field testing, restoration and replacement of defective base post(s), and all materials, equipment, and work incidental thereto.

Pay Factor Scale: Work shall be considered defective whenever the base post length or base post embedment depth is less than the specified length by more than 2 inches. If the number of defects results in rejection, the Contractor shall remove and replace all metal sign base posts on the Project, at no cost to the Department.

Number of Posts to be Tested and Pay Factors (Based on Number of Defects)

Number of Posts in Project =>	51-100	101-250	251-1000	>1000
Sample Size=>	5 Posts	10 Posts	40 Posts	60 Posts
0 Defects	1.0	1.0	1.025	1.025
1 Defect	0.9	0.95	0.975	0.983
2 Defects	Rejection	0.9	0.95	0.967
3 Defects	Rejection	Rejection	0.925	0.95
4 Defects	Rejection	Rejection	0.9	0.933
5 Defects	Rejection	Rejection	Rejection	0.917
6 Defects	Rejection	Rejection	Rejection	0.9
7 or more Defects	Rejection	Rejection	Rejection	Rejection

Note: Projects with 50 or fewer posts will not include field testing.

ITEM 1800001A RADAR SPEED DISPLAY SIGNS (SOLAR POWERED)

DESCRIPTION:

The work shall consist of furnishing and installing LED Radar Speed Display Signs and their associated power supplies in accordance with the contract documents or as directed by the Engineer.

MATERIALS:

The Contractor shall furnish LED Radar Speed Display Signs in accordance to these requirements:

The digital display shall consist of amber LEDs and have a full letter height of 12-inches and shall be capable of displaying 2-digits. The display shall be capable of displaying a "SLOW DOWN" message using a 3-inch letter height, if the detected speed is more than 10 MPH above the posted speed limit. The speed shall be displayed in 1 MPH increments.

The LED Radar Speed Display Sign shall be mounted on and a ConnDOT Standard Traffic sign post. The bottom of the speed feedback shall be mounted 7'-0" above finished grade, per MUTCD. A speed limit (R2-I) sign shall be mounted above the speed feedback sign.

The speed feedback sign shall have the words "YOUR SPEED" in black letters and a white background. The sheeting shall meet the requirements of the Standard Specifications.

The battery shall be a user-replaceable battery rated at 30 AH or higher.

Power supply shall be one solar (330 watt minimum) panel array with a bracket for mounting on top of the sign post. Flexible, liquid tight conduit shall be utilized from the solar panel to the weatherhead on the pole or as instructed by solar

The Support for Sign shall be galvanized and powder coated with at least two coats of exterior grade powder coat paint suitable for a low speed traffic environment subject to high levels of salt. All steel components, except for stainless steel and anchor plates, shall be galvanized, pre-treated, and shop painted except as noted. Hardware need not be painted after galvanizing except for the portions exposed to view after installation, such as bolt heads, ends, nuts, and washers, which may be field painted. Touch-up and repairs shall be made using paint from the same batch run as used for the shop-applied coats and supplied by the shop applicator.

All wiring shall be considered incidental to the cost for the Radar Speed Display Sign. All materials furnished, assembled, installed and used in the fabrication and erection of the Radar Speed Display Sign shall be new and installed per the contract documents and manufacturer's instructions. Materials not specifically covered in these specifications shall be in accordance with the current, accepted standards of the National Electric Manufacturers Association (NEMA), the Underwriters Laboratories (UL), the National Electric Code (NEC) and the American Society for

Testing and Materials (ASTM).

CONSTRUCTION METHODS:

The wiring of the speed feedback sign shall be completed by a Connecticut Licensed Electrician.

The Contractor shall orient the fixtures in such a manner as to optimize viewing and detection angles using the manufacturer's recommendations for installation instructions.

The Contractor shall conduct approved stand-alone, system performance tests of the equipment installed. The tests shall, as a minimum, satisfactorily exercise all stand-alone functional requirements of the field equipment. Following successful completion of the system performance tests, a 90 calendar-day test shall be performed. The purpose of the operational test is to demonstrate reliability of the system equipment for a 90-day period. Final acceptance shall be based on the satisfactory completion of the 90-day test.

The setup and programming of the speed feedback sign shall be completed and coordinated by the Contractor. The display options shall be coordinated with the Trumbull Engineering Department.

METHOD OF MEASUREMENT:

This work will be measured for payment by the number of RADAR SPEED DISPLAY SIGN - SOLAR POWERED installed, completed and accepted.

BASIS OF PAYMENT:

This work will be paid for at the contract unit price each for " RADAR SPEED DISPLAY SIGN - SOLAR POWERED" completed and accepted in place, which price shall include all materials, equipment, tools and labor incidental thereto.